

#\$+K!

Object Graphics Library 3.0

Julian Smart

September 1998

Contents

[Introduction](#)

[OGLEdit: a sample OGL application](#)

[Class reference](#)

[Topic overviews](#)

[Bugs](#)

[Change log](#)

C ontents
C ontents
b rowse00001
K Contents
D isableButton("Up")

Introduction

Object Graphics Library (OGL) is a C++ library supporting the creation and manipulation of simple and complex graphic images on a canvas.

It can be found in the directory `utils/ogl/src` in the wxWindows distribution. The file `ogl.h` must be included to make use of the library.

Please see [OGL overview](#) for a general description how the object library works. For details, please see the [class reference](#).

File structure

Introduction
topic0
browse00002
K Introduction
DisableButton("Up")

`##+K!` **OGLEdit: a sample OGL application**

OGLEdit is a sample OGL application that allows the user to draw, edit, save and load a few shapes. It should clarify aspects of OGL usage, and can act as a template for similar applications. OGLEdit can be found in `samples/ogledit` in the OGL distribution.

`{bmc ogledit.bmp}`

The wxWindows document/view model has been used in OGL, to reduce the amount of housekeeping logic required to get it up and running. OGLEdit also provides a demonstration of the Undo/Redo capability supported by the document/view classes, and how a typical application might implement this feature.

[OGLEdit files](#)

[How OGLEdit works](#)

[Possible enhancements](#)

`O`GLEdit: a sample OGL application

`o`gledit

`b`rowse00004

`K` OGLEdit a sample OGL application

`D`isableButton("Up")

##+K! **Class reference**

These are the main OGL classes.

[wxOGLConstraint](#)

[wxBitmapShape](#)

[wxDiagram](#)

[wxDrawnShape](#)

[wxCircleShape](#)

[wxCompositeShape](#)

[wxDividedShape](#)

[wxDivisionShape](#)

[wxEllipseShape](#)

[wxLineShape](#)

[wxPolygonShape](#)

[wxRectangleShape](#)

[wxPseudoMetaFile](#)

[wxShape](#)

[wxShapeCanvas](#)

[wxShapeEvtHandler](#)

[wxTextShape](#)

[Functions](#)

Class reference

Classref

browse00008

K Class reference

DisableButton("Up")

Topic overviews

The following sections describe particular topics.

[OGL overview](#)

[wxDividedShape overview](#)

[wxCompositeShape overview](#)

T
opic overviews
t
opic295
b
rowse00393
K
Topic overviews
D
isableButton("Up")

Bugs

These are the known bugs.

{bmc bullet.bmp} In the OGLEdit sample, .dia files are output double-spaced due to an unidentified bug in the way a stream is converted to a file.

Bugs
bugs
rowse00397
K Bugs
DisableButton("Up")

Change log

Version 3.0, September 8th 1998

{bmc bullet.bmp} Version for wxWindows 2.0.

{bmc bullet.bmp} Various enhancements especially to wxDrawnShape (multiple metafiles, for different orientations).

{bmc bullet.bmp} More ability to override functions e.g. OnSizeDragLeft, so events can be intercepted for Do/Undo.

Version 2.0, June 1st 1996

{bmc bullet.bmp} First publicly released version.

C_hange log
t_opic296
b_rowse00398
K_Change log
D_isableButton("Up")

File structure

These are the files that comprise the OGL library.

basic.h Header for basic objects such as wxShape and wxRectangleShape.

basic.cpp Basic objects implementation (1).

basic2.cpp Basic objects implementation (2).

bmpshape.h wxBitmapShape class header.

bmpshape.cpp wxBitmapShape implementation.

canvas.h wxShapeCanvas class header.

canvas.cpp wxShapeCanvas class implementation.

composit.h Composite object class header.

composit.cpp Composite object class implementation.

constrnt.h Constraint classes header.

constrnt.cpp Constraint classes implementation.

divided.h Divided object class header.

divided.cpp Divided object class implementation.

drawn.h Drawn (metafile) object class header.

drawn.cpp Drawn (metafile) object class implementation.

graphics.h Main include file.

lines.h wxLineShape class header.

lines.cpp wxLineShape class implementation.

misc.h Miscellaneous graphics functions header.

misc.cpp Miscellaneous graphics functions implementation.

ogldiag.h wxDiagram class header.

ogldiag.cpp wxDiagram implementation.

mfutils.h Metafile utilities header.

F
ile structure

t
opic1

b
rowse00003

K
File structure

E
nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `topic0)")

mfutils.cpp Metafile utilities implementation.

OGLEdit files

OGLEdit comprises the following source files.

{bmc bullet.bmp} doc.h, doc.cpp: MyDiagram, DiagramDocument, DiagramCommand, MyEvtHandler classes related to diagram functionality and documents.

{bmc bullet.bmp} view.h, view.cpp: MyCanvas, DiagramView classes related to visualisation of the diagram.

{bmc bullet.bmp} ogleedit.h, ogleedit.cpp: MyFrame, MyApp classes related to the overall application.

{bmc bullet.bmp} palette.h, palette.cpp: EditorToolPalette implementing the shape palette.

OGLEdit files

topic2

browse00005

OGLEdit files

enableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `ogleedit')")

How OGLEdit works

OGLEdit defines a DiagramDocument class, each of instance of which holds a MyDiagram member which itself contains the shapes.

In order to implement specific mouse behaviour for shapes, a class MyEvtHandler is defined which is 'plugged into' each shape when it is created, instead of overriding each shape class individually. This event handler class also holds a label string.

The DiagramCommand class is the key to implementing Undo/Redo. Each instance of DiagramCommand stores enough information about an operation (create, delete, change colour etc.) to allow it to carry out (or undo) its command. In DiagramView::OnMenuCommand, when the user initiates the command, a new DiagramCommand instance is created which is then sent to the document's command processor (see wxWindows manual for more information about doc/view and command processing).

Apart from menu commands, another way commands are initiated is by the user left-clicking on the canvas or right-dragging on a node. MyCanvas::OnLeftClick in view.cpp shows how the appropriate wxClassInfo is passed to a DiagramCommand, to allow DiagramCommand::Do to create a new shape given the wxClassInfo.

The MyEvtHandler right-drag methods in doc.cpp implement drawing a line between two shapes, detecting where the right mouse button was released and looking for a second shape. Again, a new DiagramCommand instance is created and passed to the command processor to carry out the command.

DiagramCommand::Do and DiagramCommand::Undo embody much of the interesting interaction with the OGL library. A complication of note when implementing undo is the problem of deleting a node shape which has one or more arcs attached to it. If you delete the node, the arc(s) should be deleted too. But multiple arc deletion represents more information that can be incorporated in the existing DiagramCommand scheme. OGLEdit copes with this by treating each arc deletion as a separate command, and sending Cut commands recursively, providing an undo path. Undoing such a Cut will only undo one command at a time - not a one to one correspondence with the original command - but it's a reasonable compromise and preserves Do/Undo while keeping our DiagramCommand class simple.

How OGLEdit works

topic3

browse00006

K How OGLEdit works

EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `ogledit')")

Possible enhancements

OGLEdit is very simplistic and does not employ the more advanced features of OGL, such as:

- {bmc bullet.bmp} attachment points (arcs are drawn to particular points on a shape)
- {bmc bullet.bmp} metafile and bitmaps shapes
- {bmc bullet.bmp} divided rectangles
- {bmc bullet.bmp} composite shapes, and constraints
- {bmc bullet.bmp} creating labels in shape regions
- {bmc bullet.bmp} arc labels (OGL has support for three movable labels per arc)
- {bmc bullet.bmp} spline and multiple-segment line arcs
- {bmc bullet.bmp} adding annotations to node and arc shapes
- {bmc bullet.bmp} line-straightening (supported by OGL) and alignment (not supported directly by OGL)

These could be added to OGLEdit, at the risk of making it a less useful example for beginners.

Possible enhancements

topic4

browse00007

K Possible enhancements

EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `ogledit')")

`wxOGLConstraint`

[{bmc books.bmp}wxCompositeShape overview](#)

An `wxOGLConstraint` object helps specify how child shapes are laid out with respect to siblings and parents.

Derived from

`wxObject`

See also

[wxCompositeShape](#)

Members

[wxOGLConstraint::wxOGLConstraint](#)
[wxOGLConstraint::~~wxOGLConstraint](#)
[wxOGLConstraint::Equals](#)
[wxOGLConstraint::Evaluate](#)
[wxOGLConstraint::SetSpacing](#)

`wxOGLConstraint`

`wxoglconstraint`

`rowse00009`

`wxOGLConstraint`

`enableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `classref)")`

`wxBitmapShape`

Draws a bitmap (non-resizable).

Derived from

[wxRectangleShape](#)

Members

[wxBitmapShape::wxBitmapShape](#)

[wxBitmapShape::~wxBitmapShape](#)

[wxBitmapShape::GetBitmap](#)

[wxBitmapShape::GetFilename](#)

[wxBitmapShape::SetBitmap](#)

[wxBitmapShape::SetFilename](#)

`wxBitmapShape`

`wxbitmapshape`

`browse00015`

`K wxBitmapShape`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `classref)")`

#+K1 **wxDiagram**

Encapsulates an entire diagram, with methods for reading/writing and drawing. A diagram has an associated wxShapeCanvas.

Derived from

wxObject

See also

[wxShapeCanvas](#)

Members

[wxDiagram::wxDiagram](#)
[wxDiagram::~~wxDiagram](#)
[wxDiagram::AddShape](#)
[wxDiagram::Clear](#)
[wxDiagram::DeleteAllShapes](#)
[wxDiagram::DrawOutline](#)
[wxDiagram::FindShape](#)
[wxDiagram::GetCanvas](#)
[wxDiagram::GetCount](#)
[wxDiagram::GetGridSpacing](#)
[wxDiagram::GetMouseTolerance](#)
[wxDiagram::GetShapeList](#)
[wxDiagram::GetQuickEditMode](#)
[wxDiagram::GetSnapToGrid](#)
[wxDiagram::InsertShape](#)
[wxDiagram::LoadFile](#)
[wxDiagram::OnDatabaseLoad](#)
[wxDiagram::OnDatabaseSave](#)
[wxDiagram::OnHeaderLoad](#)
[wxDiagram::OnHeaderSave](#)
[wxDiagram::OnShapeLoad](#)
[wxDiagram::OnShapeSave](#)
[wxDiagram::ReadContainerGeometry](#)
[wxDiagram::ReadLines](#)
[wxDiagram::ReadNodes](#)
[wxDiagram::RecentreAll](#)
[wxDiagram::Redraw](#)
[wxDiagram::RemoveAllShapes](#)
[wxDiagram::RemoveShape](#)

wxDiagram

wxdiagram

browse00022

K wxDiagram

EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `classref)")

wxDiagram::SaveFile
wxDiagram::SetCanvas
wxDiagram::SetGridSpacing
wxDiagram::SetMouseTolerance
wxDiagram::SetQuickEditMode
wxDiagram::SetSnapToGrid
wxDiagram::ShowAll
wxDiagram::Snap

#+K1 wxDrawnShape

Draws a pseudo-metafile shape, which can be loaded from a simple Windows metafile.

wxDrawnShape allows you to specify a different shape for each of four orientations (North, West, South and East). It also provides a set of drawing functions for programmatic drawing of a shape, so that during construction of the shape you can draw into it as if it were a device context.

Derived from

[wxRectangleShape](#)

See also [wxRectangleShape](#).

Members

[wxDrawnShape::wxDrawnShape](#)
[wxDrawnShape::~~wxDrawnShape](#)
[wxDrawnShape::CalculateSize](#)
[wxDrawnShape::DestroyClippingRect](#)
[wxDrawnShape::DrawArc](#)
[wxDrawnShape::DrawAtAngle](#)
[wxDrawnShape::DrawEllipticArc](#)
[wxDrawnShape::DrawLine](#)
[wxDrawnShape::DrawLines](#)
[wxDrawnShape::DrawPoint](#)
[wxDrawnShape::DrawPolygon](#)
[wxDrawnShape::DrawRectangle](#)
[wxDrawnShape::DrawRoundedRectangle](#)
[wxDrawnShape::DrawSpline](#)
[wxDrawnShape::DrawText](#)
[wxDrawnShape::GetAngle](#)
[wxDrawnShape::GetMetaFile](#)
[wxDrawnShape::GetRotation](#)
[wxDrawnShape::LoadFromMetaFile](#)
[wxDrawnShape::Rotate](#)
[wxDrawnShape::SetClippingRect](#)
[wxDrawnShape::SetDrawnBackgroundColour](#)
[wxDrawnShape::SetDrawnBackgroundMode](#)
[wxDrawnShape::SetDrawnBrush](#)
[wxDrawnShape::SetDrawnFont](#)
[wxDrawnShape::SetDrawnPen](#)
[wxDrawnShape::SetDrawnTextColour](#)

wxDrawnShape

wxdrawnshape

browse00060

K wxDrawnShape

EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `classref)")

wxDrawnShape::Scale

wxDrawnShape::SetSaveToFile

wxDrawnShape::Translate

`$$$KL` **wxCircleShape**

An wxEllipseShape whose width and height are the same.

Derived from

[wxEllipseShape](#).

Members

[wxCircleShape::wxCircleShape](#)

[wxCircleShape::~~wxCircleShape](#)

`wxCircleShape`
`wxcircleshape`
`brorowse00091`
`K wxCircleShape`
`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `classref)")`

\$#+K1. **wxCompositeShape**

This is an object with a list of child objects, and a list of size and positioning constraints between the children.

Derived from

[wxRectangleShape](#)

See also

[wxCompositeShape overview](#)

Members

[wxCompositeShape::wxCompositeShape](#)
[wxCompositeShape::~~wxCompositeShape](#)
[wxCompositeShape::AddChild](#)
[wxCompositeShape::AddConstraint](#)
[wxCompositeShape::CalculateSize](#)
[wxCompositeShape::ContainsDivision](#)
[wxCompositeShape::DeleteConstraint](#)
[wxCompositeShape::DeleteConstraintsInvolvingChild](#)
[wxCompositeShape::FindConstraint](#)
[wxCompositeShape::FindContainerImage](#)
[wxCompositeShape::GetConstraints](#)
[wxCompositeShape::GetDivisions](#)
[wxCompositeShape::MakeContainer](#)
[wxCompositeShape::OnCreateDivision](#)
[wxCompositeShape::Recompute](#)
[wxCompositeShape::RemoveChild](#)

^wxCompositeShape
^wxcompositeshape
^browse00094
^K wxCompositeShape
^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `classref)")

`wxDividedShape`

A `wxDividedShape` is a rectangle with a number of vertical divisions. Each division may have its text formatted with independent characteristics, and the size of each division relative to the whole image may be specified.

Derived from

[`wxRectangleShape`](#)

See also

[`wxDividedShape` overview](#)

Members

[`wxDividedShape::wxDividedShape`](#)

[`wxDividedShape::~~wxDividedShape`](#)

[`wxDividedShape::EditRegions`](#)

[`wxDividedShape::SetRegionSizes`](#)

`wxDividedShape`

`wxdividedshape`

`rowse00111`

`wxDividedShape`

`enableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `classref)")`

\$#+K1 **wxDivisionShape**

A division shape is like a composite in that it can contain further objects, but is used exclusively to divide another shape into regions, or divisions. A wxDivisionShape is never free-standing.

Derived from

[wxCompositeShape](#)

See also

[wxCompositeShape overview](#)

Members

[wxDivisionShape::wxDivisionShape](#)
[wxDivisionShape::~~wxDivisionShape](#)
[wxDivisionShape::AdjustBottom](#)
[wxDivisionShape::AdjustLeft](#)
[wxDivisionShape::AdjustRight](#)
[wxDivisionShape::AdjustTop](#)
[wxDivisionShape::Divide](#)
[wxDivisionShape::EditEdge](#)
[wxDivisionShape::GetBottomSide](#)
[wxDivisionShape::GetHandleSide](#)
[wxDivisionShape::GetLeftSide](#)
[wxDivisionShape::GetLeftSideColour](#)
[wxDivisionShape::GetLeftSidePen](#)
[wxDivisionShape::GetRightSide](#)
[wxDivisionShape::GetTopSide](#)
[wxDivisionShape::GetTopSideColour](#)
[wxDivisionShape::GetTopSidePen](#)
[wxDivisionShape::ResizeAdjoining](#)
[wxDivisionShape::PopupMenu](#)
[wxDivisionShape::SetBottomSide](#)
[wxDivisionShape::SetHandleSide](#)
[wxDivisionShape::SetLeftSide](#)
[wxDivisionShape::SetLeftSideColour](#)
[wxDivisionShape::SetLeftSidePen](#)
[wxDivisionShape::SetRightSide](#)
[wxDivisionShape::SetTopSide](#)
[wxDivisionShape::SetTopSideColour](#)
[wxDivisionShape::SetTopSidePen](#)

^wxDivisionShape

^wxdivisionshape

^browse00116

^K wxDivisionShape

^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `classref)")

`wxEllipseShape`

The `wxEllipseShape` behaves similarly to the `wxRectangleShape` but is elliptical.

Derived from

[`wxShape`](#)

Members

[`wxEllipseShape::wxEllipseShape`](#)

[`wxEllipseShape::~~wxEllipseShape`](#)

`wxEllipseShape`

`wxellipseshape`

`rowse00145`

`wxEllipseShape`

`enableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `classref)")`

\$#+K1 **wxLineShape**

A wxLineShape may be attached to two nodes; it may be segmented, in which case a control point is drawn for each joint.

A wxLineShape may have arrows at the beginning, end and centre.

Derived from

[wxShape](#)

Members

[wxLineShape::wxLineShape](#)
[wxLineShape::~~wxLineShape](#)
[wxLineShape::AddArrow](#)
[wxLineShape::AddArrowOrdered](#)
[wxLineShape::ClearArrow](#)
[wxLineShape::ClearArrowsAtPosition](#)
[wxLineShape::DrawArrow](#)
[wxLineShape::DeleteArrowHead](#)
[wxLineShape::DeleteLineControlPoint](#)
[wxLineShape::DrawArrows](#)
[wxLineShape::DrawRegion](#)
[wxLineShape::EraseRegion](#)
[wxLineShape::FindArrowHead](#)
[wxLineShape::FindLineEndPoints](#)
[wxLineShape::FindLinePosition](#)
[wxLineShape::FindMinimumWidth](#)
[wxLineShape::FindNth](#)
[wxLineShape::GetAttachmentFrom](#)
[wxLineShape::GetAttachmentTo](#)
[wxLineShape::GetEnds](#)
[wxLineShape::GetFrom](#)
[wxLineShape::GetLabelPosition](#)
[wxLineShape::GetNextControlPoint](#)
[wxLineShape::GetTo](#)
[wxLineShape::Initialise](#)
[wxLineShape::InsertLineControlPoint](#)
[wxLineShape::IsEnd](#)
[wxLineShape::IsSpline](#)
[wxLineShape::MakeLineControlPoints](#)
[wxLineShape::OnMoveLink](#)
[wxLineShape::SetAttachmentFrom](#)

^wxLineShape

^wxlineshape

^browse00148

^K wxLineShape

^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `classref)")

wxLineStyle::SetAttachments
wxLineStyle::SetAttachmentTo
wxLineStyle::SetEnds
wxLineStyle::SetFrom
wxLineStyle::SetIgnoreOffsets
wxLineStyle::SetSpline
wxLineStyle::SetTo
wxLineStyle::Straighten
wxLineStyle::Unlink

`wxPolygonShape`

A `wxPolygonShape`'s shape is defined by a number of points passed to the object's constructor. It can be used to create new shapes such as diamonds and triangles.

Derived from

[wxShape](#)

Members

[wxPolygonShape::wxPolygonShape](#)
[wxPolygonShape::~~wxPolygonShape](#)
[wxPolygonShape::Create](#)
[wxPolygonShape::AddPolygonPoint](#)
[wxPolygonShape::CalculatePolygonCentre](#)
[wxPolygonShape::DeletePolygonPoint](#)
[wxPolygonShape::GetPoints](#)
[wxPolygonShape::UpdateOriginalPoints](#)

`wxPolygonShape`
`wxpolygonshape`
`rowse00189`
`K wxPolygonShape`
`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `classref)")`

`$$$KL` **wxRectangleShape**

The wxRectangleShape has rounded or square corners.

Derived from

[wxShape](#)

Members

[wxRectangleShape::wxRectangleShape](#)

[wxRectangleShape::~~wxRectangleShape](#)

[wxRectangleShape::SetCornerRadius](#)

`w`xRectangleShape

`w`xrectangleshape

`b`rowse00198

`K` wxRectangleShape

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `classref)")

\$#+K1. **wxPseudoMetaFile**

A simple metafile-like class which can load data from a Windows metafile on all platforms.

Derived from

wxObject

w_xPseudoMetaFile
w_xpseudometafile
b_rowse00202
K wxPseudoMetaFile
E_nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `classref)")

\$#+K1 **wxShape**

The wxShape is the top-level, abstract object that all other objects are derived from. All common functionality is represented by wxShape's members, and overridden members that appear in derived classes and have behaviour as documented for wxShape, are not documented separately.

Derived from

[wxShapeEvtHandler](#)

Members

[wxShape::wxShape](#)
[wxShape::~~wxShape](#)
[wxShape::AddLine](#)
[wxShape::AddRegion](#)
[wxShape::AddText](#)
[wxShape::AddToCanvas](#)
[wxShape::AncestorSelected](#)
[wxShape::ApplyAttachmentOrdering](#)
[wxShape::AssignNewIds](#)
[wxShape::Attach](#)
[wxShape::AttachmentIsValid](#)
[wxShape::AttachmentSortTest](#)
[wxShape::CalcSimpleAttachment](#)
[wxShape::CalculateSize](#)
[wxShape::ClearAttachments](#)
[wxShape::ClearRegions](#)
[wxShape::ClearText](#)
[wxShape::Constrain](#)
[wxShape::Copy](#)
[wxShape::CreateNewCopy](#)
[wxShape::DeleteControlPoints](#)
[wxShape::Detach](#)
[wxShape::Draggable](#)
[wxShape::Draw](#)
[wxShape::DrawContents](#)
[wxShape::DrawLinks](#)
[wxShape::Erase](#)
[wxShape::EraseContents](#)
[wxShape::EraseLinks](#)
[wxShape::FindRegion](#)
[wxShape::FindRegionNames](#)

^wxShape

^wxshape

^browse00203

^K wxShape

^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `classref)")

[wxShape::Flash](#)
[wxShape::FormatText](#)
[wxShape::GetAttachmentMode](#)
[wxShape::GetAttachmentPosition](#)
[wxShape::GetBoundingBoxMax](#)
[wxShape::GetBoundingBoxMin](#)
[wxShape::GetBrush](#)
[wxShape::GetCanvas](#)
[wxShape::GetCentreResize](#)
[wxShape::GetChildren](#)
[wxShape::GetClientData](#)
[wxShape::GetDisableLabel](#)
[wxShape::GetEventHandler](#)
[wxShape::GetFixedHeight](#)
[wxShape::GetFixedSize](#)
[wxShape::GetFixedWidth](#)
[wxShape::GetFont](#)
[wxShape::GetFunctor](#)
[wxShape::GetId](#)
[wxShape::GetLinePosition](#)
[wxShape::GetLines](#)
[wxShape::GetMaintainAspectRatio](#)
[wxShape::GetNumberOfAttachments](#)
[wxShape::GetNumberOfTextRegions](#)
[wxShape::GetParent](#)
[wxShape::GetPen](#)
[wxShape::GetPerimeterPoint](#)
[wxShape::GetRegionId](#)
[wxShape::GetRegionName](#)
[wxShape::GetRegions](#)
[wxShape::GetRotation](#)
[wxShape::GetSensitivityFilter](#)
[wxShape::GetShadowMode](#)
[wxShape::GetSpaceAttachments](#)
[wxShape::GetTextColour](#)
[wxShape::GetTopAncestor](#)
[wxShape::GetX](#)
[wxShape::GetY](#)
[wxShape::HitTest](#)
[wxShape::Insert](#)
[wxShape::IsHighlighted](#)
[wxShape::IsShown](#)
[wxShape::MakeControlPoints](#)
[wxShape::MakeMandatoryControlPoints](#)
[wxShape::Move](#)
[wxShape::MoveLineToNewAttachment](#)
[wxShape::MoveLinks](#)
[wxShape::NameRegions](#)
[wxShape::Rotate](#)
[wxShape::ReadConstraints](#)
[wxShape::ReadAttributes](#)

wxShape::ReadRegions
wxShape::Recentre
wxShape::RemoveFromCanvas
wxShape::ResetControlPoints
wxShape::ResetMandatoryControlPoints
wxShape::Recompute
wxShape::RemoveLine
wxShape::Select
wxShape::Selected
wxShape::SetAttachmentMode
wxShape::SetBrush
wxShape::SetCanvas
wxShape::SetCentreResize
wxShape::SetClientData
wxShape::SetDefaultRegionSize
wxShape::SetDisableLabel
wxShape::SetDraggable
wxShape::SetDrawHandles
wxShape::SetEventHandler
wxShape::SetFixedSize
wxShape::SetFont
wxShape::SetFormatMode
wxShape::SetHighlight
wxShape::SetId
wxShape::SetMaintainAspectRatio
wxShape::SetPen
wxShape::SetRegionName
wxShape::SetSensitivityFilter
wxShape::SetShadowMode
wxShape::SetSize
wxShape::SetSpaceAttachments
wxShape::SetTextColour
wxShape::SetX
wxShape::SetX
wxShape::SpaceAttachments
wxShape::Show
wxShape::Unlink
wxShape::WriteAttributes
wxShape::WriteRegions

\$#+K1 **wxShapeCanvas**

A canvas for drawing diagrams on.

Derived from

wxScrolledWindow

See also

[wxDiagram](#)

Members

[wxShapeCanvas::wxShapeCanvas](#)
[wxShapeCanvas::~~wxShapeCanvas](#)
[wxShapeCanvas::AddShape](#)
[wxShapeCanvas::FindShape](#)
[wxShapeCanvas::FindFirstSensitiveShape](#)
[wxShapeCanvas::GetDiagram](#)
[wxShapeCanvas::GetGridSpacing](#)
[wxShapeCanvas::GetMouseTolerance](#)
[wxShapeCanvas::GetShapeList](#)
[wxShapeCanvas::GetQuickEditMode](#)
[wxShapeCanvas::InsertShape](#)
[wxShapeCanvas::OnBeginDragLeft](#)
[wxShapeCanvas::OnBeginDragRight](#)
[wxShapeCanvas::OnEndDragLeft](#)
[wxShapeCanvas::OnEndDragRight](#)
[wxShapeCanvas::OnDragLeft](#)
[wxShapeCanvas::OnDragRight](#)
[wxShapeCanvas::OnLeftClick](#)
[wxShapeCanvas::OnRightClick](#)
[wxShapeCanvas::Redraw](#)
[wxShapeCanvas::RemoveShape](#)
[wxShapeCanvas::SetDiagram](#)
[wxShapeCanvas::Snap](#)

w wxShapeCanvas

w wxshapecanvas

b rowse00325

K wxShapeCanvas

E `nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `classref)")`

`wxShapeEvtHandler`

`wxShapeEvtHandler` is a class from which `wxShape` (and therefore all shape classes) are derived. A `wxShape` also contains a pointer to its current `wxShapeEvtHandler`. Event handlers can be swapped in and out, altering the behaviour of a shape. This allows, for example, a range of behaviours to be redefined in one class, rather than requiring each shape class to be subclassed.

Derived from

`wxObject`

Members

[`wxShapeEvtHandler::m_handlerShape`](#)
[`wxShapeEvtHandler::m_previousHandler`](#)
[`wxShapeEvtHandler::wxShapeEvtHandler`](#)
[`wxShapeEvtHandler::~wxShapeEvtHandler`](#)
[`wxShapeEvtHandler::CopyData`](#)
[`wxShapeEvtHandler::CreateNewCopy`](#)
[`wxShapeEvtHandler::GetPreviousHandler`](#)
[`wxShapeEvtHandler::GetShape`](#)
[`wxShapeEvtHandler::OnBeginDragLeft`](#)
[`wxShapeEvtHandler::OnBeginDragRight`](#)
[`wxShapeEvtHandler::OnBeginSize`](#)
[`wxShapeEvtHandler::OnChangeAttachment`](#)
[`wxShapeEvtHandler::OnDragLeft`](#)
[`wxShapeEvtHandler::OnDragRight`](#)
[`wxShapeEvtHandler::OnDraw`](#)
[`wxShapeEvtHandler::OnDrawContents`](#)
[`wxShapeEvtHandler::OnDrawControlPoints`](#)
[`wxShapeEvtHandler::OnDrawOutline`](#)
[`wxShapeEvtHandler::OnEndDragLeft`](#)
[`wxShapeEvtHandler::OnEndDragRight`](#)
[`wxShapeEvtHandler::OnEndSize`](#)
[`wxShapeEvtHandler::OnErase`](#)
[`wxShapeEvtHandler::OnEraseContents`](#)
[`wxShapeEvtHandler::OnEraseControlPoints`](#)
[`wxShapeEvtHandler::OnHighlight`](#)
[`wxShapeEvtHandler::OnLeftClick`](#)
[`wxShapeEvtHandler::OnMoveLink`](#)
[`wxShapeEvtHandler::OnMoveLinks`](#)
[`wxShapeEvtHandler::OnMovePost`](#)
[`wxShapeEvtHandler::OnMovePre`](#)

`wxShapeEvtHandler`

`wxshapeevthandler`

`rowse00349`

`wxShapeEvtHandler`

`enableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `classref)")`

wxShapeEvtHandler::OnRightClick
wxShapeEvtHandler::OnSize
wxShapeEvtHandler::OnSizingBeginDragLeft
wxShapeEvtHandler::OnSizingDragLeft
wxShapeEvtHandler::OnSizingEndDragLeft
wxShapeEvtHandler::SetPreviousHandler
wxShapeEvtHandler::SetShape

wxTextShape

As wxRectangleShape, but only the text is displayed.

Derived from

[wxRectangleShape](#)

Members

[wxTextShape::wxTextShape](#)

[wxTextShape::~~wxTextShape](#)

w_xTextShape
w_xtextshape
b_rowse00387
K wxTextShape
E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `classref)")

\$#+K! **Functions**

These are the OGL functions.

[::wxOGLInitialize](#)
[::wxOGLCleanUp](#)

F
unctions
f
unctions
b
rowse00390
K
Functions
E
nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `classref)")

OGL overview

wxShapeCanvas, derived from **wxCanvas**, is the drawing area for a number of wxShape instances. Everything drawn on a wxShapeCanvas is derived from wxShape, which provides virtual member functions for redrawing, creating and destroying resize/selection 'handles', movement and erasing behaviour, mouse click behaviour, calculating the bounding box of the shape, linking nodes with arcs, and so on.

The way a client application copes with 'damage' to the canvas is to erase (white out) anything should no longer be displayed, redraw the shape, and then redraw everything on the canvas to repair any damage. If quick edit mode is on for the canvas, the complete should be omitted by OGL and the application.

Selection handles (called control points in the code) are implemented as wxRectangleShapes.

Events are passed to shapes by the canvas in a high-level form, for example **OnLeftClick**, **OnBeginDragLeft**, **OnDragLeft**, **OnEndDragLeft**. The canvas decides what is a click and what is a drag, whether it is on a shape or the canvas itself, and (by interrogating the shape) which attachment point the click is associated with.

In order to provide event-handling flexibility, each shapes has an 'event handler' associated with it, which by default is the shape itself (all shapes derive from wxShapeEvtHandler). An application can modify the event-handling behaviour simply by plugging a new event handler into the shape. This can avoid the need for multiple inheritance when new properties and behaviour are required for a number of different shape classes: instead of overriding each class, one new event handler class can be defined and used for all existing shape classes.

A range of shapes have been predefined in the library, including rectangles, ellipses, polygons. A client application can derive from these shapes and/or derive entirely new shapes from wxShape.

Instances of a class called wxDiagram organise collections of shapes, providing default file input and output behaviour.

OGL overview

ogloverview

browse00394

K OGL overview

EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `topic295')")

wxDividedShape overview

Classes: [wxDividedShape](#)

A wxDividedShape is a rectangle with a number of vertical divisions. Each division may have its text formatted with independent characteristics, and the size of each division relative to the whole image may be specified.

Once a wxDividedShape has been created, the user may move the divisions with the mouse. By pressing Ctrl while right-clicking, the region attributes can be edited.

Here are examples of creating wxDividedShape objects:

```
/*
 * Divided rectangle with 3 regions
 */

wxDividedShape *dividedRect = new wxDividedShape(50, 60);

wxShapeRegion *region = new wxShapeRegion;
region->SetProportions(0.0, 0.25);
dividedRect->AddRegion(region);

region = new wxShapeRegion;
region->SetProportions(0.0, 0.5);
dividedRect->AddRegion(region);

region = new wxShapeRegion;
region->SetProportions(0.0, 0.25);
dividedRect->AddRegion(region);

dividedRect->SetSize(50, 60); // Allow it to calculate region
sizes
dividedRect->SetPen(wxBLACK_PEN);
dividedRect->SetBrush(wxWHITE_BRUSH);
dividedRect->Show(TRUE);
dividedRect->NameRegions();

/*
 * Divided rectangle with 3 regions, rounded
 */

wxDividedShape *dividedRect3 = new wxDividedShape(50, 60);
dividedRect3->SetCornerRadius(-0.4);

region = new wxShapeRegion;
region->SetProportions(0.0, 0.25);
dividedRect3->AddRegion(region);

region = new wxShapeRegion;
```

[wxDividedShape overview](#)

[dividedshapeoverview](#)

[browse00395](#)

[wxDividedShape overview](#)

[enableButton\("Up"\);ChangeButtonBinding\("Up", "JumpId\(^ogl.hlp', `topic295'\)"\)](#)

```
region->SetProportions(0.0, 0.5);
dividedRect3->AddRegion(region);

region = new wxShapeRegion;
region->SetProportions(0.0, 0.25);
dividedRect3->AddRegion(region);

dividedRect3->SetSize(50, 60); // Allow it to calculate region
sizes
dividedRect3->SetPen(wxBLACK_PEN);
dividedRect3->SetBrush(wxWHITE_BRUSH);
dividedRect3->Show(TRUE);
dividedRect3->NameRegions();
```

`wxCompositeShape` overview

Classes: [wxCompositeShape](#), [wxOGLConstraint](#)

The `wxCompositeShape` allows fairly complex shapes to be created, and maintains a set of constraints which specify the layout and proportions of child shapes.

Add child shapes to a `wxCompositeShape` using [AddChild](#), and add constraints using [AddConstraint](#).

After children and shapes have been added, call [Recompute](#) which will return TRUE if the constraints could be satisfied, FALSE otherwise. If constraints have been correctly and consistently specified, this call will succeed.

If there is more than one child, constraints must be specified: OGL cannot calculate the size and position of children otherwise. Don't assume that children will simply move relative to the parent without the use of constraints.

To specify a constraint, you need three things:

1. a constraint type, such as `gyCONSTRAINT_CENTRED_VERTICALLY`;
2. a reference shape, with respect to which other shapes are going to be positioned - the *constraining* shape;
3. a list of one or more shapes to be constrained: the *constrained* shapes.

The constraining shape can be either the parent of the constrained shapes, or a sibling. The constrained shapes must all be siblings of each other.

For an exhaustive list and description of the available constraint types, see the [wxOGLConstraint constructor](#). Note that most constraints operate in one dimension only (vertically or horizontally), so you will usually need to specify constraints in pairs.

You can set the spacing between constraining and constrained shapes by calling [wxOGLConstraint::SetSpacing](#).

Finally, a `wxCompositeShape` can have *divisions*, which are special child shapes of class `wxDivisionShape` (not to be confused with `wxDividedShape`). The purpose of this is to allow the composite to be divided into user-adjustable regions (divisions) into which other shapes can be dropped dynamically, given suitable application code. Divisions allow the child shapes to have an identity of their own - they can be manipulated independently of their container - but to behave as if they are contained with the division, moving with the parent shape. Divisions boundaries can themselves be moved using the mouse.

`wxCompositeShape` overview

compositeshapeoverview

rowse00396

`wxCompositeShape` overview

`enableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `topic295')")`

To create an initial division, call wxCompositeShape::MakeContainer. Make further divisions by calling wxDivisionShape::Divide.

`$#+K!` **wxOGLConstraint::wxOGLConstraint**

wxOGLConstraint()^K

Default constructor.

wxOGLConstraint(int *type*, wxShape **constraining*, wxList& *constrained*)^K

Constructor.

Parameters

constraining

The shape which is used as the reference for positioning the *constrained* objects.

constrained

Contains a list of wxShapes which are to be constrained (with respect to *constraining*) using *type*.

type

Can be one of:

{bmc bullet.bmp} **gyCONSTRAINT_CENTRED_VERTICALLY**: the Y co-ordinates of the centres of the bounding boxes of the constrained objects and the constraining object will be the same

{bmc bullet.bmp} **gyCONSTRAINT_CENTRED_HORIZONTALLY**: the X co-ordinates of the centres of the bounding boxes of the constrained objects and the constraining object will be the same

{bmc bullet.bmp} **gyCONSTRAINT_CENTRED_BOTH**: the co-ordinates of the centres of the bounding boxes of the constrained objects and the constraining object will be the same

{bmc bullet.bmp} **gyCONSTRAINT_LEFT_OF**: the X co-ordinates of the right hand vertical edges of the bounding boxes of the constrained objects will be less than the X co-ordinate of the left hand vertical edge of the bounding box of the constraining object

{bmc bullet.bmp} **gyCONSTRAINT_RIGHT_OF**: the X co-ordinates of the left hand vertical edges of the bounding boxes of the constrained objects will be greater than the X co-ordinate of the right hand vertical edge of the

`w_xOGLConstraint::wxOGLConstraint`

`w_xoglconstraintconstr`

`b_rowse00010`

`K wxOGLConstraint wxOGLConstraint`

`E_nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxoglconstraint')")`

`K wxOGLConstraint`

`K wxOGLConstraint`

bounding box of the constraining object

{bmc bullet.bmp} **gyCONSTRAINT_ABOVE**: the Y co-ordinates of the bottom horizontal edges of the bounding boxes of the constrained objects will be less than the Y co-ordinate of the top horizontal edge of the bounding box of the constraining object

{bmc bullet.bmp} **gyCONSTRAINT_BELOW**: the Y co-ordinates of the top horizontal edges of the bounding boxes of the constrained objects will be greater than the X co-ordinate of the bottom horizontal edge of the bounding box of the constraining object

{bmc bullet.bmp} **gyCONSTRAINT_ALIGNED_TOP**: the Y co-ordinates of the top horizontal edges of the bounding boxes of the constrained objects will be the same as the Y co-ordinate of the top horizontal edge of the bounding box of the constraining object

{bmc bullet.bmp} **gyCONSTRAINT_ALIGNED_BOTTOM**: the Y co-ordinates of the bottom horizontal edges of the bounding boxes of the constrained objects will be the same as the Y co-ordinate of the bottom horizontal edge of the bounding box of the constraining object

{bmc bullet.bmp} **gyCONSTRAINT_ALIGNED_LEFT**: the X co-ordinates of the left hand vertical edges of the bounding boxes of the constrained objects will be the same as the X co-ordinate of the left hand vertical edge of the bounding box of the constraining object

{bmc bullet.bmp} **gyCONSTRAINT_ALIGNED_RIGHT**: the X co-ordinates of the right hand vertical edges of the bounding boxes of the constrained objects will be the same as the X co-ordinate of the right hand vertical edge of the bounding box of the constraining object

{bmc bullet.bmp} **gyCONSTRAINT_MIDALIGNED_TOP**: the Y co-ordinates of the centres of the bounding boxes of the constrained objects will be the same as the Y co-ordinate of the top horizontal edge of the bounding box of the constraining object

{bmc bullet.bmp} **gyCONSTRAINT_MIDALIGNED_BOTTOM**: the Y co-ordinates of the centres of the bounding boxes of the constrained objects will be the same as the Y co-ordinate of the bottom horizontal edge of the bounding box of the constraining object

{bmc bullet.bmp} **gyCONSTRAINT_MIDALIGNED_LEFT**: the X co-ordinates of the centres of the bounding boxes of the constrained objects will be the same as the X co-ordinate of the left hand vertical edge of the bounding box of the constraining object

{bmc bullet.bmp} **gyCONSTRAINT_MIDALIGNED_RIGHT**: the X co-ordinates of the centres of the bounding boxes of the constrained objects will be the same as the X co-ordinate of the right hand vertical edge of the bounding box of the constraining object

`$#+K! wxOGLConstraint::~~wxOGLConstraint`

`~wxOGLConstraint()K`

Destructor.

`w_xOGLConstraint::~~wxOGLConstraint`

`topic5`

`browse00011`

`K wxOGLConstraint ~wxOGLConstraint`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxoglconstraint')")`

`K ~wxOGLConstraint`

`##+K! wxOGLConstraint::Equals`

`bool Equals(double x, double y)K`

Returns TRUE if *x* and *y* are approximately equal (for the purposes of evaluating the constraint).

`w_xOGLConstraint::Equals`

`topic6`

`browse00012`

`K wxOGLConstraint Equals`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxoglconstraint')")`

`K Equals`

`$#+K!` **wxOGLConstraint::Evaluate**

bool Evaluate()^K

Evaluates this constraint, returning TRUE if anything changed.

`w` **wxOGLConstraint::Evaluate**

`t` **opic7**

`b` **rowse00013**

`K` **wxOGLConstraint Evaluate**

`E` **nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxoglconstraint')")**

`K` **Evaluate**

`$#+K!` **wxOGLConstraint::SetSpacing**

void SetSpacing(double x, double y)^K

Sets the horizontal and vertical spacing for the constraint.

^w wxOGLConstraint::SetSpacing

^w wxoglconstraintsetspacing

^b rowse00014

^K wxOGLConstraint SetSpacing

^E nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxoglconstraint')")

^K SetSpacing

`$#+K!` **wxBitmapShape::wxBitmapShape**

wxBitmapShape()^K

Constructor.

`w`xBitmapShape::wxBitmapShape

`t`opic8

`b`rowse00016

`K` wxBitmapShape wxBitmapShape

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxbitmapshape')")

`K` wxBitmapShape

`$#+K!` **wxBitmapShape::~~wxBitmapShape**

`~wxBitmapShape()`^K

Destructor.

`w`xBitmapShape::~~wxBitmapShape

`t`opic9

`b`rowse00017

`K` wxBitmapShape ~wxBitmapShape

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxbitmapshape')")

`K` ~wxBitmapShape

`wxBitmapShape::GetBitmap`

`wxBitmap& GetBitmap() const`

Returns a reference to the bitmap associated with this shape.

```
wxBitmapShape::GetBitmap
topic10
browse00018
K wxBitmapShape GetBitmap
K GetBitmap
E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxbitmapshape')")
```

`wxBitmapShape::GetFilename`

`wxString GetFilename() const`

Returns the bitmap filename.

`wxBitmapShape::GetFilename`
topic11
browse00019
K wxBitmapShape GetFilename
K GetFilename
E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxbitmapshape')")

`wxBitmapShape::SetBitmap`

`void SetBitmap(const wxBitmap& bitmap)K`

Sets the bitmap associated with this shape. You can delete the bitmap from the calling application, since reference counting will take care of holding on to the internal bitmap data.

`wxBitmapShape::SetBitmap`
`topic12`
`browse00020`
`K wxBitmapShape SetBitmap`
`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxbitmapshape')")`
`K SetBitmap`

`wxBitmapShape::SetFilename`

`void SetFilename(const wxString& filename)`

Sets the bitmap filename.

`wxBitmapShape::SetFilename`

`topic13`

`browse00021`

`wxBitmapShape SetFilename`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxbitmapshape')")`

`SetFilename`

`$#+K!` wxDiagram::wxDiagram

`wxDiagram()`^K

Constructor.

`wxDiagram::wxDiagram`

`topic14`

`browse00023`

`K wxDiagram wxDiagram`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdiagram')")`

`K wxDiagram`

`$#+K! wxDiagram::~~wxDiagram`

`~wxDiagram()`^K

Destructor.

`wxDiagram::~~wxDiagram`

`topic15`

`browser00024`

`K wxDiagram ~wxDiagram`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdiagram')")`

`K ~wxDiagram`

`$$$K! wxDiagram::AddShape`

`void AddShape(wxShape* shape, wxShape *addAfter = NULL)K`

Adds a shape to the diagram. If *addAfter* is non-NULL, the shape will be added after this one.

`w`xDiagram::AddShape
`t`opic16
`b`rowse00025
`K` wxDiagram AddShape
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdiagram')")
`K` AddShape

`$#+K1` **wxDiagram::Clear**

void Clear(wxDC& dc)^K

Clears the specified device context.

`wxDiagram::Clear`

`topic17`

`browse00026`

`K wxDiagram Clear`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdiagram')")`

`K Clear`

wxDiagram::DeleteAllShapes

void DeletesAllShapes()

Removes and deletes all shapes in the diagram.

wxDiagram::DeleteAllShapes

topic18

browse00027

wxDiagram DeleteAllShapes

enableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp`, `wxdiagram`)")

DeletesAllShapes

`wxDiagram::DrawOutline`

`void DrawOutline(wxDC& dc, double x1, double y1, double x2, double y2)`^K

Draws an outline rectangle on the current device context.

`wxDiagram::DrawOutline`

`topic19`

`browse00028`

`K wxDiagram DrawOutline`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdiagram')")`

`K DrawOutline`

`$#+KKl wxDiagram::FindShape`

`wxShape* FindShape(long id) const`

Returns the shape for the given identifier.

`wxDiagram::FindShape`

`wxdiagramfindshape`

`rowse00029`

`K wxDiagram FindShape`

`K FindShape`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdiagram')")`

`##+KK1 wxDiagram::GetCanvas`

`wxShapeCanvas* GetCanvas() const`

Returns the shape canvas associated with this diagram.

`wxDiagram::GetCanvas`
`topic20`
`browse00030`
`K wxDiagram GetCanvas`
`K GetCanvas`
`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdiagram')")`

`$#+KKl wxDiagram::GetCount`

`int GetCount() const`

Returns the number of shapes in the diagram.

`w_xDiagram::GetCount`
`w_xdiagramgetcount`
`browse00031`
`K wxDiagram GetCount`
`K GetCount`
`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdiagram')")`

`##+KK1 wxDiagram::GetGridSpacing`

`double GetGridSpacing() const`

Returns the grid spacing.

w_xDiagram::GetGridSpacing
t_opic21
b_rowse00032
K wxDiagram GetGridSpacing
K GetGridSpacing
E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdiagram')")

`##+K! wxDiagram::GetMouseTolerance`

`int GetMouseTolerance()`^K

Returns the tolerance within which a mouse move is ignored.

`w`xDiagram::GetMouseTolerance
`t`opic22
`b`rowse00033
`K` wxDiagram GetMouseTolerance
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdiagram')")
`K` GetMouseTolerance

`$$$K1 wxDiagram::GetShapeList`

`wxList* GetShapeList() const`

Returns a pointer to the internal shape list.

`wxDiagram::GetShapeList`

`topic23`

`browse00034`

`K wxDiagram GetShapeList`

`K GetShapeList`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdiagram')")`

`$$$K1 wxDiagram::GetQuickEditMode`

`bool GetQuickEditMode() const`

Returns quick edit mode.

`w`xDiagram::GetQuickEditMode
`t`opic24
`b`rowse00035
`K` wxDiagram GetQuickEditMode
`K` GetQuickEditMode
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdiagram')")

`##+KK! wxDiagram::GetSnapToGrid`

`bool GetSnapToGrid() const`

Returns snap-to-grid mode.

`wxDiagram::GetSnapToGrid`

`topic25`

`browse00036`

`K wxDiagram GetSnapToGrid`

`K GetSnapToGrid`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdiagram')")`

`wxDiagram::InsertShape`

`void InsertShape(wxShape *shape)`^K

Inserts a shape at the front of the shape list.

`wxDiagram::InsertShape`

`topic26`

`browse00037`

`wxDiagram InsertShape`

`enableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdiagram')")`

`InsertShape`

`$#+K!` **wxDiagram::LoadFile**

bool LoadFile(const wxString& filename)^K

Loads the diagram from a file.

`w`xDiagram::LoadFile

`t`opic27

`b`rowse00038

`K` wxDiagram LoadFile

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdiagram')")

`K` LoadFile

`wxDiagram::OnDatabaseLoad`

`void OnDatabaseLoad(wxExprDatabase& database)`^K

Called just after the nodes and lines have been read from the `wxExprDatabase`. You may override this; the default member does nothing.

`wxDiagram::OnDatabaseLoad`
topic28
browse00039
K wxDiagram OnDatabaseLoad
E nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdiagram')")
K OnDatabaseLoad

`wxDiagram::OnDatabaseSave`

`void OnDatabaseSave(wxExprDatabase& database)`^K

Called just after the nodes and lines have been written to the `wxExprDatabase`. You may override this; the default member does nothing.

`wxDiagram::OnDatabaseSave`
topic29
browse00040
K wxDiagram OnDatabaseSave
E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdiagram')")
K OnDatabaseSave

`$#+K!` **wxDiagram::OnHeaderLoad**

bool OnHeaderLoad(wxExprDatabase& *database*, wxExpr& *expr*)^K

Called to allow the 'diagram' header object to be read. The default member reads no further information. You may wish to override this to read version information, author name, etc.

`wxDiagram::OnHeaderLoad`
`topic30`
`browse00041`
`K wxDiagram OnHeaderLoad`
`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdiagram')")`
`K OnHeaderLoad`

\$\$\$K! wxDiagram::OnHeaderSave

bool OnHeaderSave(wxExprDatabase& database, wxExpr& expr)^K

Called to allow instantiation of the 'diagram' header object. The default member writes no further information. You may wish to override this to include version information, author name, etc.

wxDiagram::OnHeaderSave
topic31
browse00042
K wxDiagram OnHeaderSave
EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdiagram')")
K OnHeaderSave

`$$$K! wxDiagram::OnShapeLoad`

`bool OnShapeLoad(wxExprDatabase& database, wxShape& shape, wxExpr& expr)K`

Called to read the shape from the *expr*. You may override this, but call this function first. The default member calls `ReadAttributes` for the shape.

`wxDiagram::OnShapeLoad`
`topic32`
`browse00043`
`K wxDiagram OnShapeLoad`
`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdiagram')")`
`K OnShapeLoad`

`wxDiagram::OnShapeSave`

`bool OnShapeSave(wxExprDatabase& database, wxShape& shape, wxExpr& expr)`^K

Called to save the shape to the *expr* and *database*. You may override this, but call this function first. The default member calls `WriteAttributes` for the shape, appends the shape to the database, and if the shape is a composite, recursively calls `OnShapeSave` for its children.

`wxDiagram::OnShapeSave`

`topic33`

`browse00044`

`wxDiagram OnShapeSave`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdiagram')")`

`OnShapeSave`

`wxDiagram::ReadContainerGeometry`

`void ReadContainerGeometry(wxExprDatabase& database)`^K

Reads container geometry from a `wxExprDatabase`, linking up nodes which are part of a composite. You probably won't need to redefine this.

`wxDiagram::ReadContainerGeometry`
topic34
browse00045
K wxDiagram ReadContainerGeometry
E nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdiagram')")
K ReadContainerGeometry

`$#+K!` **wxDiagram::ReadLines**

void ReadLines(wxExprDatabase& database)^K

Reads lines from a wxExprDatabase. You probably won't need to redefine this.

`w`xDiagram::ReadLines

`t`opic35

`b`rowse00046

`K` wxDiagram ReadLines

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdiagram')")

`K` ReadLines

`$$$K! wxDiagram::ReadNodes`

`void ReadNodes(wxExprDatabase& database)K`

Reads nodes from a wxExprDatabase. You probably won't need to redefine this.

`wxDiagram::ReadNodes`

`topic36`

`browse00047`

`K wxDiagram ReadNodes`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdiagram')")`

`K ReadNodes`

`$#+K!` **wxDiagram::RecentreAll**

void RecentreAll(wxDC& dc)^K

Make sure all text that should be centred, is centred.

`wxDiagram::RecentreAll`

`topic37`

`browse00048`

`K wxDiagram RecentreAll`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdiagram')")`

`K RecentreAll`

`wxDiagram::Redraw`

`void Redraw(wxDC& dc)`

Draws the shapes in the diagram on the specified device context.

`wxDiagram::Redraw`
`topic38`
`browse00049`
`K wxDiagram Redraw`
`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdiagram')")`
`K Redraw`

wxDiagram::RemoveAllShapes

void RemoveAllShapes()

Removes all shapes from the diagram but does not delete the shapes.

wxDiagram::RemoveAllShapes
topic39
browse00050
K wxDiagram RemoveAllShapes
E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdiagram')")
K RemoveAllShapes

`wxDiagram::RemoveShape`

`void RemoveShape(wxShape* shape)`^K

Removes the shape from the diagram (non-recursively) but does not delete it.

`wxDiagram::RemoveShape`

`topic40`

`browse00051`

`wxDiagram RemoveShape`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdiagram')")`

`RemoveShape`

`$$$K! wxDiagram::SaveFile`

`bool SaveFile(const wxString& filename)K`

Saves the diagram in a file.

`wxDiagram::SaveFile`

`topic41`

`browse00052`

`K wxDiagram SaveFile`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdiagram')")`

`K SaveFile`

`wxDiagram::SetCanvas`

`void SetCanvas(wxShapeCanvas* canvas)`^K

Sets the canvas associated with this diagram.

^w`xDiagram::SetCanvas`

^w`xdiagramsetcanvas`

^b`rowse00053`

^K `wxDiagram SetCanvas`

^E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdiagram')")`

^K `SetCanvas`

`wxDiagram::SetGridSpacing`

`void SetGridSpacing(double spacing)`^K

Sets the grid spacing. The default is 5.

`wxDiagram::SetGridSpacing`

`topic42`

`browse00054`

`K wxDiagram SetGridSpacing`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdiagram')")`

`K SetGridSpacing`

`##+K! wxDiagram::SetMouseTolerance`

`void SetMouseTolerance(int tolerance)K`

Sets the tolerance within which a mouse move is ignored. The default is 3 pixels.

`w`xDiagram::SetMouseTolerance
`t`opic43
`b`rowse00055
`K` wxDiagram SetMouseTolerance
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdiagram')")
`K` SetMouseTolerance

`$#+K!` **wxDiagram::SetQuickEditMode**

void SetQuickEditMode(bool *mode*)^K

Sets quick-edit-mode on or off. In this mode, refreshes are minimized, but the diagram may need manual refreshing occasionally.

`wxDiagram::SetQuickEditMode`
`topic44`
`browse00056`
`K wxDiagram SetQuickEditMode`
`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdiagram')")`
`K SetQuickEditMode`

`$#+K!` **wxDiagram::SetSnapToGrid**

void SetSnapToGrid(bool *snap*)^K

Sets snap-to-grid mode on or off. The default is on.

`wxDiagram::SetSnapToGrid`
`topic45`
`browse00057`
`K wxDiagram SetSnapToGrid`
`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdiagram')")`
`K SetSnapToGrid`

`$#+K!` **wxDiagram::ShowAll**

void ShowAll(**bool** *show*)^K

Calls Show for each shape in the diagram.

`w`xDiagram::ShowAll

`t`opic46

`b`rowse00058

`K` wxDiagram ShowAll

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdiagram')")

`K` ShowAll

`##+K! wxDiagram::Snap`

`void Snap(double *x, double *y)K`

'Snaps' the coordinate to the nearest grid position, if snap-to-grid is on.

`wxDiagram::Snap`

`topic47`

`rowse00059`

`K wxDiagram Snap`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdiagram')")`

`K Snap`

`$#+K!` **wxDrawnShape::wxDrawnShape**

wxDrawnShape()^K

Constructor.

`w`xDrawnShape::wxDrawnShape

`t`opic48

`b`rowse00061

`K` wxDrawnShape wxDrawnShape

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp`, `wxdrawnshape`)")

`K` wxDrawnShape

`$#+K! wxDrawnShape::~~wxDrawnShape`

`~wxDrawnShape()K`

Destructor.

`wxDrawnShape::~~wxDrawnShape`

`topic49`

`browse00062`

`K wxDrawnShape ~wxDrawnShape`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdrawnshape')")`

`K ~wxDrawnShape`

`wxDrawnShape::CalculateSize`

`void CalculateSize()`

Calculates the wxDrawnShape size from the current metafile. Call this after you have drawn into the shape.

`wxDrawnShape::CalculateSize`
`topic50`
`browse00063`
`K wxDrawnShape CalculateSize`
`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdrawnshape`)")`
`K CalculateSize`

`wxDrawnShape::DestroyClippingRect`

`void DestroyClippingRect()`^K

Destroys the clipping rectangle. See also [`wxDrawnShape::SetClippingRect`](#).

^w`wxDrawnShape::DestroyClippingRect`

^w`wxdrawshapedestroyclippingrect`

^b`rowse00064`

^K`wxDrawnShape DestroyClippingRect`

^E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdrawnshape')")`

^K`DestroyClippingRect`

`$$$K! wxDrawnShape::DrawArc`

`void DrawArc(const wxPoint& centrePoint, const wxPoint& startPoint, const wxPoint& endPoint)K`

Draws an arc (see wxWindows documentation for details).

`w_xDrawnShape::DrawArc`
`w_xdrawnshapedrawarc`
`browse00065`
`K wxDrawnShape DrawArc`
`E_nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdrawnshape')")`
`K DrawArc`

`wxDrawnShape::DrawAtAngle`

`void DrawAtAngle(int angle)`^K

Sets the metafile for the given orientation, which can be one of:

`{bmc bullet.bmp} ogIDRAWN_ANGLE_0`

`{bmc bullet.bmp} ogIDRAWN_ANGLE_90`

`{bmc bullet.bmp} ogIDRAWN_ANGLE_180`

`{bmc bullet.bmp} ogIDRAWN_ANGLE_270`

See also [`wxDrawnShape::GetAngle`](#).

^w`wxDrawnShape::DrawAtAngle`

^w`wxdrawshapedrawatangle`

^b`rowse00066`

^K`wxDrawnShape DrawAtAngle`

^E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdrawnshape')")`

^K`DrawAtAngle`

`$#+K!` **wxDrawnShape::DrawEllipticArc**

void DrawEllipticArc(const wxRect& *rect*, double *startAngle*, double *endAngle*)^K

Draws an elliptic arc (see wxWindows documentation for details).

^wxDrawnShape::DrawEllipticArc

^wxdrawnshapedrawellipticarc

^browse00067

^K wxDrawnShape DrawEllipticArc

^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdrawnshape')")

^K DrawEllipticArc

`$$$K! wxDrawnShape::DrawLine`

`void DrawLine(const wxPoint& point1, const wxPoint& point2)K`

Draws a line from *point1* to *point2*.

`w_xDrawnShape::DrawLine`

`w_xdrawnshapedrawline`

`b_rowse00068`

`K wxDrawnShape DrawLine`

`E_nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdrawnshape')")`

`K DrawLine`

`wxDrawnShape::DrawLines`

`void DrawLines(int n, wxPoint& points[])`^K

Draws *n* lines.

`wxDrawnShape::DrawLines`
`wxdrawshapedrawlines`
`rowse00069`
`wxDrawnShape DrawLines`
`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdrawnshape')")`
`DrawLines`

`wxDrawnShape::DrawPoint`

`void DrawPoint(const wxPoint& point)`^K

Draws a point.

^w`wxDrawnShape::DrawPoint`

^w`wxdrawshapedrawpoint`

^b`rowse00070`

^K`wxDrawnShape DrawPoint`

^E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdrawnshape')")`

^K`DrawPoint`

`wxDrawnShape::DrawPolygon`

`void DrawPolygon(int n, wxPoint& points[], int flags = 0)`

Draws a polygon. *flags* can be one or more of `ogIMETAFLAGS_OUTLINE` (use this polygon for the drag outline) and `ogIMETAFLAGS_ATTACHMENTS` (use the vertices of this polygon for attachments).

`wxDrawnShape::DrawPolygon`
`wxdrawshapedrawpolygon`
`rowse00071`
`wxDrawnShape DrawPolygon`
`enableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdrawnshape')")`
`DrawPolygon`

`$#+K!` **wxDrawnShape::DrawRectangle**

void DrawRectangle(const wxRect& *rect*)^K

Draws a rectangle.

^wxDrawnShape::DrawRectangle

^wxdrawshapedrawrectangle

^browse00072

^K wxDrawnShape DrawRectangle

^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdrawnshape')")

^K DrawRectangle

`$#+K!` **wxDrawnShape::DrawRoundedRectangle**

void DrawRoundedRectangle(const wxRect& *rect*, double *radius*)^K

Draws a rounded rectangle. *radius* is the corner radius. If *radius* is negative, it expresses the radius as a proportion of the smallest dimension of the rectangle.

`w`xDrawnShape::DrawRoundedRectangle
`w`xdrawnshapedrawroundedrectangle
`b`rowse00073
`K` wxDrawnShape DrawRoundedRectangle
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdrawnshape')")
`K` DrawRoundedRectangle

`$#+K!` **wxDrawnShape::DrawSpline**

void DrawSpline(int *n*, wxPoint& *points[]*)^K

Draws a spline curve.

^wxDrawnShape::DrawSpline

^wxdrawnshapedrawspline

^browse00074

^K wxDrawnShape DrawSpline

^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdrawnshape')")

^K DrawSpline

^{S#+K!}**wxDrawnShape::DrawText**

void DrawText(const wxString& *text*, const wxPoint& *point*)^K

Draws text at the given point.

^wwxDrawnShape::DrawText

^wwxdrawshapedrawtext

^browse00075

^KwxDrawnShape DrawText

^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdrawnshape')")

^KDrawText

`wxDrawnShape::GetAngle`

`int GetAngle() const`

Returns the current orientation, which can be one of:

`{bmc bullet.bmp} ogIDRAWN_ANGLE_0`

`{bmc bullet.bmp} ogIDRAWN_ANGLE_90`

`{bmc bullet.bmp} ogIDRAWN_ANGLE_180`

`{bmc bullet.bmp} ogIDRAWN_ANGLE_270`

See also [`wxDrawnShape::DrawAtAngle`](#).

`wxDrawnShape::GetAngle`

`wxdrawnshapegetangle`

`rowse00076`

`wxDrawnShape GetAngle`

`GetAngle`

`enableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdrawnshape')")`

`##+KK1 wxDrawnShape::GetMetaFile`

`wxPseudoMetaFile& GetMetaFile() const`

Returns a reference to the internal 'pseudo-metafile'.

`wxDrawnShape::GetMetaFile`

`topic51`

`browse00077`

`K wxDrawnShape GetMetaFile`

`K GetMetaFile`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdrawnshape`)")`

`##+KK1 wxDrawnShape::GetRotation`

`double GetRotation() const`

Returns the current rotation of the shape in radians.

`w_xDrawnShape::GetRotation`

`w_xdrawnshapegetrotation`

`browse00078`

`K wxDrawnShape GetRotation`

`K GetRotation`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdrawnshape')")`

`wxDrawnShape::LoadFromMetaFile`

`bool LoadFromMetaFile(const wxString& filename)`^K

Loads a (very simple) Windows metafile, created for example by Top Draw, the Windows shareware graphics package.

`wxDrawnShape::LoadFromMetaFile`

`topic52`

`browse00079`

`wxDrawnShape LoadFromMetaFile`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdrawnshape`)")`

`LoadFromMetaFile`

`wxDrawnShape::Rotate`

`void Rotate(double x, double y, double theta)`

Rotate about the given axis by the given amount in radians.

`wxDrawnShape::Rotate`

`topic53`

`rowse00080`

`wxDrawnShape Rotate`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdrawnshape')")`

`Rotate`

`wxDrawnShape::SetClippingRect`

`void SetClippingRect(const wxRect& rect)`^K

Sets the clipping rectangle. See also [`wxDrawnShape::DestroyClippingRect`](#).

^w`wxDrawnShape::SetClippingRect`

^w`wxdrawshapsetclippingrect`

^b`rowse00081`

^K `wxDrawnShape SetClippingRect`

^E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdrawnshape')")`

^K `SetClippingRect`

`wxDrawnShape::SetDrawnBackgroundColour`

`void SetDrawnBackgroundColour(const wxColour& colour)`^K

Sets the current background colour for the current metafile.

^w`wxDrawnShape::SetDrawnBackgroundColour`

^w`wxdrawshapsetdrawnbackgroundcolour`

^b`rowse00082`

^K`wxDrawnShape SetDrawnBackgroundColour`

^E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdrawnshape')")`

^K`SetDrawnBackgroundColour`

`$$$K! wxDrawnShape::SetDrawnBackgroundMode`

`void SetDrawnBackgroundMode(int mode)K`

Sets the current background mode for the current metafile.

`w_xDrawnShape::SetDrawnBackgroundMode`
`w_xdrawnshapersetdrawnbackgroundmode`
`browse00083`
`K wxDrawnShape SetDrawnBackgroundMode`
`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdrawnshape')")`
`K SetDrawnBackgroundMode`

`$#+K!` **wxDrawnShape::SetDrawnBrush**

void SetDrawnBrush(wxPen* pen, bool isOutline = FALSE)^K

Sets the pen for this metafile. If *isOutline* is TRUE, this pen is taken to indicate the outline (and if the outline pen is changed for the whole shape, the pen will be replaced with the outline pen).

`w`xDrawnShape::SetDrawnBrush
`w`xdrawshapetdrawnbrush
`b`rowse00084
`K` wxDrawnShape SetDrawnBrush
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdrawnshape')")
`K` SetDrawnBrush

`$#+K!` wxDrawnShape::SetDrawnFont

`void SetDrawnFont(wxFont* font)`^K

Sets the current font for the current metafile.

`w`xDrawnShape::SetDrawnFont
`w`xdrawshapsetdrawnfont
`b`rowse00085
`K` wxDrawnShape SetDrawnFont
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdrawnshape')")
`K` SetDrawnFont

`$$$K! wxDrawnShape::SetDrawnPen`

`void SetDrawnPen(wxPen* pen, bool isOutline = FALSE)K`

Sets the pen for this metafile. If *isOutline* is TRUE, this pen is taken to indicate the outline (and if the outline pen is changed for the whole shape, the pen will be replaced with the outline pen).

`w_xDrawnShape::SetDrawnPen`
`w_xdrawnshapersetdrawnpen`
`b_rowse00086`
`K wxDrawnShape SetDrawnPen`
`E_nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdrawnshape')")`
`K SetDrawnPen`

`$#+K!` **wxDrawnShape::SetDrawnTextColour**

void SetDrawnTextColour(const wxColour& *colour*)^K

Sets the current text colour for the current metafile.

^wxDrawnShape::SetDrawnTextColour

^wxdrawshapsetdrawntextcolour

^browse00087

^K wxDrawnShape SetDrawnTextColour

^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdrawnshape')")

^K SetDrawnTextColour

`wxDrawnShape::Scale`

`void Scale(double sx, double sy)`

Scales the shape by the given amount.

`wxDrawnShape::Scale`

`topic54`

`browse00088`

`wxDrawnShape Scale`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdrawnshape')")`

`Scale`

`$#+K!` **wxDrawnShape::SetSaveToFile**

void SetSaveToFile(bool *save*)^K

If *save* is TRUE, the image will be saved along with the shape's other attributes. The reason why this might not be desirable is that if there are many shapes with the same image, it would be more efficient for the application to save one copy, and not duplicate the information for every shape. The default is TRUE.

`w`xDrawnShape::SetSaveToFile
`t`opic55
`b`rowse00089
`K` wxDrawnShape SetSaveToFile
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdrawnshape')")
`K` SetSaveToFile

`wxDrawnShape::Translate`

`void Translate(double x, double y)`

Translates the shape by the given amount.

`wxDrawnShape::Translate`

`topic56`

`browse00090`

`wxDrawnShape Translate`

`enableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdrawnshape')")`

`Translate`

`wxCircleShape::wxCircleShape`

`wxCircleShape(double width = 0.0)`

Constructor.

`wxCircleShape::wxCircleShape`

`topic57`

`browse00092`

`wxCircleShape wxCircleShape`

`enableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxcircleshape')")`

`wxCircleShape`

`$#+K! wxCircleShape::~~wxCircleShape`

`~wxCircleShape()`^K

Destructor.

`wxCircleShape::~~wxCircleShape`

`topic58`

`browse00093`

`K wxCircleShape ~wxCircleShape`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxcircleshape')")`

`K ~wxCircleShape`

`##+K! wxCompositeShape::wxCompositeShape`

`wxCompositeShape()`^K

Constructor.

`wxCompositeShape::wxCompositeShape`

`topic59`

`browse00095`

`K wxCompositeShape wxCompositeShape`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxcompositeshape')")`

`K wxCompositeShape`

`$#+K! wxCompositeShape::~~wxCompositeShape`

`~wxCompositeShape()K`

Destructor.

`wxCompositeShape::~~wxCompositeShape`

`topic60`

`browse00096`

`K wxCompositeShape ~wxCompositeShape`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxcompositeshape')")`

`K ~wxCompositeShape`

`wxCompositeShape::AddChild`

`void AddChild(wxShape *child, wxShape *addAfter = NULL)`^K

Adds a child shape to the composite. If *addAfter* is non-NULL, the shape will be added after this shape.

^w`wxCompositeShape::AddChild`
^w`wxcompositeshapeaddchild`
^b`rowse00097`
^K `wxCompositeShape AddChild`
^E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxcompositeshape')")`
^K `AddChild`

`wxCompositeShape::AddConstraint`

`wxOGLConstraint * AddConstraint(wxOGLConstraint *constraint)`^K

`wxOGLConstraint * AddConstraint(int type, wxShape *constraining, wxList&constrained)`^K

`wxOGLConstraint * AddConstraint(int type, wxShape *constraining, wxShape *constrained)`^K

Adds a constraint to the composite.

`wxCompositeShape::AddConstraint`

`wxcompositeshapeaddconstraint`

`rowse00098`

`wxCompositeShape AddConstraint`

`enableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxcompositeshape')")`

`AddConstraint`

`AddConstraint`

`AddConstraint`

`##+K! wxCompositeShape::CalculateSize`

`void CalculateSize()`^K

Calculates the size and position of the composite based on child sizes and positions.

`w`xCompositeShape::CalculateSize
`t`opic61
`b`rowse00099
`K` wxCompositeShape CalculateSize
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxcompositeshape')")
`K` CalculateSize

`wxCompositeShape::ContainsDivision`

`bool FindContainerImage(wxDivisionShape *division)`^K

Returns TRUE if *division* is a descendant of this container.

`wxCompositeShape::ContainsDivision`

`topic62`

`browse00100`

`wxCompositeShape ContainsDivision`

`enableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxcompositeshape')")`

`FindContainerImage`

wxCompositeShape::DeleteConstraint

void DeleteConstraint(wxOGLConstraint *constraint)^K

Deletes constraint from composite.

^wxCompositeShape::DeleteConstraint

^topic63

^browse00101

^K wxCompositeShape DeleteConstraint

^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxcompositeshape')")

^K DeleteConstraint

`wxCompositeShape::DeleteConstraintsInvolvingChild`

`void DeleteConstraintsInvolvingChild(wxShape *child)`

This function deletes constraints which mention the given child. Used when deleting a child from the composite.

`wxCompositeShape::DeleteConstraintsInvolvingChild`
`topic64`
`browse00102`
`wxCompositeShape DeleteConstraintsInvolvingChild`
`enableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxcompositeshape')")`
`DeleteConstraintsInvolvingChild`

`$#+K!` wxCompositeShape::FindConstraint

**`wxOGLConstraint * FindConstraint(long id, wxCompositeShape
actualComposite)`^K

Finds the constraint with the given id, also returning the actual composite the constraint was in, in case that composite was a descendant of this composite.

`w`xCompositeShape::FindConstraint
`t`opic65
`b`rowse00103
`K` wxCompositeShape FindConstraint
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxcompositeshape')")
`K` FindConstraint

`$#+K!` wxCompositeShape::FindContainerImage

`wxShape * FindContainerImage()`^K

Finds the image used to visualize a container. This is any child of the composite that is not in the divisions list.

`w`xCompositeShape::FindContainerImage
`t`opic66
`b`rowse00104
`K` wxCompositeShape FindContainerImage
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxcompositeshape')")
`K` FindContainerImage

`wxCompositeShape::GetConstraints`

`wxList& GetConstraints() const`

Returns a reference to the list of constraints.

`wxCompositeShape::GetConstraints`

`topic67`

`browse00105`

`K wxCompositeShape GetConstraints`

`K GetConstraints`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxcompositeshape')")`

`wxCompositeShape::GetDivisions`

`wxList& GetDivisions() const`

Returns a reference to the list of divisions.

`wxCompositeShape::GetDivisions`

`topic68`

`browse00106`

`K wxCompositeShape GetDivisions`

`K GetDivisions`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxcompositeshape')")`

`##+K! wxCompositeShape::MakeContainer`

`void MakeContainer()`^K

Makes this composite into a container by creating one child wxDivisionShape.

`w`xCompositeShape::MakeContainer
`w`xcompositeshapemakecontainer
`b`rowse00107
`K` wxCompositeShape MakeContainer
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxcompositeshape')")
`K` MakeContainer

`wxCompositeShape::OnCreateDivision`

`wxDivisionShape * OnCreateDivision()`^K

Called when a new division shape is required. Can be overridden to allow an application to use a different class of division.

`wxCompositeShape::OnCreateDivision`

`topic69`

`browse00108`

`wxCompositeShape OnCreateDivision`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxcompositeshape')")`

`OnCreateDivision`

`$#+K!` **wxCompositeShape::Recompute**

bool Recompute()^K

Recomputes any constraints associated with the object. If FALSE is returned, the constraints could not be satisfied (there was an inconsistency).

`w`xCompositeShape::Recompute
`w`xcompositeshaperecompute
`b`rowse00109
`K` wxCompositeShape Recompute
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxcompositeshape')")
`K` Recompute

`wxCompositeShape::RemoveChild`

`void RemoveChild(wxShape *child)`^K

Removes the child from the composite and any constraint relationships, but does not delete the child.

`wxCompositeShape::RemoveChild`

`topic70`

`browse00110`

`wxCompositeShape RemoveChild`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxcompositeshape)")`

`RemoveChild`

`##+K! wxDividedShape::wxDividedShape`

`wxDividedShape(double width = 0.0, double height = 0.0)`^K

Constructor.

`wxDividedShape::wxDividedShape`

`topic71`

`browse00112`

`K wxDividedShape wxDividedShape`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdividedshape')")`

`K wxDividedShape`

`$#+K! wxDividedShape::~~wxDividedShape`

`~wxDividedShape()`^K

Destructor.

`wxDividedShape::~~wxDividedShape`

`topic72`

`browse00113`

`K wxDividedShape ~wxDividedShape`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdividedshape')")`

`K ~wxDividedShape`

`$#+K!` **wxDividedShape::EditRegions**

void EditRegions()^K

Edit the region colours and styles.

`wxDividedShape::EditRegions`

`topic73`

`browse00114`

`K wxDividedShape EditRegions`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdividedshape')")`

`K EditRegions`

`wxDividedShape::SetRegionSizes`

`void SetRegionSizes()`

Set all region sizes according to proportions and this object total size.

`wxDividedShape::SetRegionSizes`

`topic74`

`browse00115`

`wxDividedShape SetRegionSizes`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdividedshape')")`

`SetRegionSizes`

`wxDivisionShape::wxDivisionShape`

`wxDivisionShape()`^K

Constructor.

`wxDivisionShape::wxDivisionShape`

`topic75`

`browse00117`

`K wxDivisionShape wxDivisionShape`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdivisionshape')")`

`K wxDivisionShape`

`wxDivisionShape::~~wxDivisionShape`

`~wxDivisionShape()`^K

Destructor.

`w`xDivisionShape::~~wxDivisionShape
`t`opic76
`b`rowse00118
`K` wxDivisionShape ~wxDivisionShape
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdivisionshape')")
`K` ~wxDivisionShape

`wxDivisionShape::AdjustBottom`

`void AdjustBottom(double bottom, bool test)`

Adjust a side, returning FALSE if it's not physically possible to adjust it to this point.

`wxDivisionShape::AdjustBottom`

`topic77`

`browse00119`

`wxDivisionShape AdjustBottom`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdivisionshape')")`

`AdjustBottom`

`$$$K! wxDivisionShape::AdjustLeft`

`void AdjustLeft(double left, bool test)K`

Adjust a side, returning FALSE if it's not physically possible to adjust it to this point.

`w_xDivisionShape::AdjustLeft`

`topic78`

`browse00120`

`K wxDivisionShape AdjustLeft`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdivisionshape')")`

`K AdjustLeft`

`wxDivisionShape::AdjustRight`

`void AdjustRight(double right, bool test)K`

Adjust a side, returning FALSE if it's not physically possible to adjust it to this point.

`wxDivisionShape::AdjustRight`

`topic79`

`browse00121`

`K wxDivisionShape AdjustRight`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdivisionshape')")`

`K AdjustRight`

`$$$K! wxDivisionShape::AdjustTop`

`void AdjustTop(double top, bool test)K`

Adjust a side, returning FALSE if it's not physically possible to adjust it to this point.

`w_xDivisionShape::AdjustTop`
`topic80`
`browse00122`
`K wxDivisionShape AdjustTop`
`E_nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdivisionshape')")`
`K AdjustTop`

`$$$K! wxDivisionShape::Divide`

`void Divide(int direction)K`

Divide this division into two further divisions, horizontally (*direction* is wxHORIZONTAL) or vertically (*direction* is wxVERTICAL).

`w_xDivisionShape::Divide`

`w_xdivisionshapedivide`

`b_rowse00123`

`K wxDivisionShape Divide`

`E_nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdivisionshape')")`

`K Divide`

`wxDivisionShape::EditEdge`

`void EditEdge(int side)`

Interactively edit style of left or top side.

`wxDivisionShape::EditEdge`
`topic81`
`browse00124`
`K wxDivisionShape EditEdge`
`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdivisionshape')")`
`K EditEdge`

`$#+K! wxDivisionShape::GetBottomSide`

`wxDivisionShape * GetBottomSide()`^K

Returns a pointer to the division on the bottom side of this division.

`w`xDivisionShape::GetBottomSide
`t`opic82
`b`rowse00125
`K` wxDivisionShape GetBottomSide
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdivisionshape')")
`K` GetBottomSide

`$#+K!` **wxDivisionShape::GetHandleSide**

int GetHandleSide()^K

Returns the side which the handle appears on (DIVISION_SIDE_LEFT or DIVISION_SIDE_TOP).

`w`xDivisionShape::GetHandleSide
`t`opic83
`b`rowse00126
`K` wxDivisionShape GetHandleSide
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdivisionshape')")
`K` GetHandleSide

`wxDivisionShape::GetLeftSide`

`wxDivisionShape * GetLeftSide()`^K

Returns a pointer to the division on the left side of this division.

`wxDivisionShape::GetLeftSide`

`topic84`

`browse00127`

`K wxDivisionShape GetLeftSide`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdivisionshape')")`

`K GetLeftSide`

`wxDivisionShape::GetLeftSideColour`

`wxString GetLeftSideColour()`^K

Returns a pointer to the colour used for drawing the left side of the division.

`wxDivisionShape::GetLeftSideColour`
topic85
browse00128
K wxDivisionShape GetLeftSideColour
E nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdivisionshape')")
K GetLeftSideColour

`$#+K! wxDivisionShape::GetLeftSidePen`

`wxPen * GetLeftSidePen()`^K

Returns a pointer to the pen used for drawing the left side of the division.

`wxDivisionShape::GetLeftSidePen`

`topic86`

`browse00129`

`K wxDivisionShape GetLeftSidePen`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdivisionshape')")`

`K GetLeftSidePen`

`$#+K! wxDivisionShape::GetRightSide`

`wxDivisionShape * GetRightSide()`^K

Returns a pointer to the division on the right side of this division.

^wxDivisionShape::GetRightSide

^topic87

^browse00130

^K wxDivisionShape GetRightSide

^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdivisionshape')")

^K GetRightSide

`wxDivisionShape::GetTopSide`

`wxDivisionShape * GetTopSide()`^K

Returns a pointer to the division on the top side of this division.

`wxDivisionShape::GetTopSide`

`topic88`

`browse00131`

`K wxDivisionShape GetTopSide`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdivisionshape')")`

`K GetTopSide`

`$#+K!` **wxDivisionShape::GetTopSideColour**

wxString GetTopSideColour()^K

Returns a pointer to the colour used for drawing the top side of the division.

`w`xDivisionShape::GetTopSideColour
`t`opic89
`b`rowse00132
`K` wxDivisionShape GetTopSideColour
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdivisionshape')")
`K` GetTopSideColour

`$#+K! wxDivisionShape::GetTopSidePen`

`wxPen * GetTopSidePen()`^K

Returns a pointer to the pen used for drawing the left side of the division.

`wxDivisionShape::GetTopSidePen`

`topic90`

`browse00133`

`K wxDivisionShape GetTopSidePen`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdivisionshape')")`

`K GetTopSidePen`

\$\$\$K! **wxDivisionShape::ResizeAdjoining**

void ResizeAdjoining(int *side*, double *newPos*, bool *test*)^K

Resize adjoining divisions at the given side. If *test* is TRUE, just see whether it's possible for each adjoining region, returning FALSE if it's not.

side can be one of:

{bmc bullet.bmp} DIVISION_SIDE_NONE

{bmc bullet.bmp} DIVISION_SIDE_LEFT

{bmc bullet.bmp} DIVISION_SIDE_TOP

{bmc bullet.bmp} DIVISION_SIDE_RIGHT

{bmc bullet.bmp} DIVISION_SIDE_BOTTOM

wxDivisionShape::ResizeAdjoining

topic91

browse00134

K wxDivisionShape ResizeAdjoining

EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdivisionshape')")

K ResizeAdjoining

`$#+K!` **wxDivisionShape::PopupMenu**

void PopupMenu(double x, double y)^K

PopupMenu the division menu.

`w`xDivisionShape::PopupMenu

`t`opic92

`b`rowse00135

`K` wxDivisionShape PopupMenu

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdivisionshape')")

`K` PopupMenu

`wxDivisionShape::SetBottomSide`

`void SetBottomSide(wxDivisionShape *shape)`

Set the pointer to the division on the bottom side of this division.

`wxDivisionShape::SetBottomSide`
`topic93`
`browse00136`
`wxDivisionShape SetBottomSide`
`enableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdivisionshape')")`
`SetBottomSide`

`$#+K!` **wxDivisionShape::SetHandleSide**

int SetHandleSide()^K

Sets the side which the handle appears on (DIVISION_SIDE_LEFT or DIVISION_SIDE_TOP).

`w`xDivisionShape::SetHandleSide
`t`opic94
`b`rowse00137
`K` wxDivisionShape SetHandleSide
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdivisionshape')")
`K` SetHandleSide

`wxDivisionShape::SetLeftSide`

`void SetLeftSide(wxDivisionShape *shape)`

Set the pointer to the division on the left side of this division.

`wxDivisionShape::SetLeftSide`

`topic95`

`browse00138`

`K wxDivisionShape SetLeftSide`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdivisionshape')")`

`K SetLeftSide`

`##+K! wxDivisionShape::SetLeftSideColour`

`void SetLeftSideColour(const wxString& colour)K`

Sets the colour for drawing the left side of the division.

`w_xDivisionShape::SetLeftSideColour`
`topic96`
`browse00139`
`K wxDivisionShape SetLeftSideColour`
`E_nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdivisionshape')")`
`K SetLeftSideColour`

`wxDivisionShape::SetLeftSidePen`

`void SetLeftSidePen(wxPen *pen)`

Sets the pen for drawing the left side of the division.

`wxDivisionShape::SetLeftSidePen`
topic97
browse00140
K wxDivisionShape SetLeftSidePen
E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdivisionshape')")
K SetLeftSidePen

`##+K! wxDivisionShape::SetRightSide`

`void SetRightSide(wxDivisionShape *shape)K`

Set the pointer to the division on the right side of this division.

`w`xDivisionShape::SetRightSide
`t`opic98
`b`rowse00141
`K` wxDivisionShape SetRightSide
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdivisionshape')")
`K` SetRightSide

`wxDivisionShape::SetTopSide`

`void SetTopSide(wxDivisionShape *shape)`

Set the pointer to the division on the top side of this division.

`wxDivisionShape::SetTopSide`

`topic99`

`browse00142`

`K wxDivisionShape SetTopSide`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdivisionshape')")`

`K SetTopSide`

`##+K! wxDivisionShape::SetTopSideColour`

`void SetTopSideColour(const wxString& colour)K`

Sets the colour for drawing the top side of the division.

`w`xDivisionShape::SetTopSideColour
`t`opic100
`b`rowse00143
`K` wxDivisionShape SetTopSideColour
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxdivisionshape')")
`K` SetTopSideColour

`wxDivisionShape::SetTopSidePen`

`void SetTopSidePen(wxPen *pen)`

Sets the pen for drawing the top side of the division.

`wxDivisionShape::SetTopSidePen`
topic101
browse00144
K wxDivisionShape SetTopSidePen
E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxdivisionshape')")
K SetTopSidePen

`$#+K!` **wxEllipseShape::wxEllipseShape**

wxEllipseShape(double width = 0.0, double height = 0.0)^K

Constructor.

wxEllipseShape::wxEllipseShape

topic102

browse00146

K wxEllipseShape wxEllipseShape

EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxellipseshape')")

K wxEllipseShape

`$#+K!` **wxEllipseShape::~~wxEllipseShape**

`~wxEllipseShape()`^K

Destructor.

`w`xEllipseShape::~~wxEllipseShape

`t`opic103

`b`rowse00147

`K` wxEllipseShape ~wxEllipseShape

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxellipseshape')")

`K` ~wxEllipseShape

`wxLineShape::wxLineShape`

`wxLineShape()`^K

Constructor.

Usually you will call `wxLineShape::MakeLineControlPoints` to specify the number of segments in the line.

`wxLineShape::wxLineShape`
topic104
browse00149
K wxLineShape wxLineShape
E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxlineshape')")
K wxLineShape

`$#+K!` **wxLineShape::~~wxLineShape**

`~wxLineShape()`^K

Destructor.

`w`xLineShape::~~wxLineShape

`t`opic105

`b`rowse00150

`K` wxLineShape ~wxLineShape

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxlineshape')")

`K` ~wxLineShape

^{S#+K!}**wxLineStyle::AddArrow**

void AddArrow(WXTYPE *type*, **bool** *end* = *ARROW_POSITION_END*, **double** *arrowSize* = 10.0, **double** *xOffset* = 0.0, **const wxString&** *name* = "", **wxPseudoMetaFile** **mf* = NULL, **long** *arrowId* = -1)^K

Adds an arrow (or annotation) to the line.

type may currently be one of:

ARROW_HOLLOW_CIRCLE Hollow circle.

ARROW_FILLED_CIRCLE Filled circle.

ARROW_ARROW Conventional arrowhead.

ARROW_SINGLE_OBLIQUE Single oblique stroke.

ARROW_DOUBLE_OBLIQUE Double oblique stroke.

ARROW_DOUBLE_METAFILE Custom arrowhead.

end may currently be one of:

ARROW_POSITION_END Arrow appears at the end.

ARROW_POSITION_START Arrow appears at the start.

arrowSize specifies the length of the arrow.

xOffset specifies the offset from the end of the line.

name specifies a name for the arrow.

mf can be a wxPseudoMetaFile, perhaps loaded from a simple Windows metafile.

arrowId is the id for the arrow.

^wwxLineStyle::AddArrow

^wwxlineshapeaddarrow

^browse00151

^KwxLineStyle AddArrow

^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxlineshape')")

^KAddArrow

^{S#+K!}**wxLineShape::AddArrowOrdered**

void AddArrowOrdered(wxArrowHead *arrow, wxList& referenceList, int end)^K

Add an arrowhead in the position indicated by the reference list of arrowheads, which contains all legal arrowheads for this line, in the correct order. E.g.

```
Reference list:    a b c d e
Current line list: a d
```

Add c, then line list is: a c d.

If no legal arrowhead position, return FALSE. Assume reference list is for one end only, since it potentially defines the ordering for any one of the 3 positions. So we don't check the reference list for arrowhead position.

^wxLineShape::AddArrowOrdered
^topic106
^browse00152
^K wxLineShape AddArrowOrdered
^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxlineshape')")
^K AddArrowOrdered

`$#+K!` **wxLineStyle::ClearArrow**

bool ClearArrow(const wxString& name)^K

Delete the arrow with the given name.

`w`xLineStyle::ClearArrow
`t`opic107
`b`rowse00153
`K` wxLineStyle ClearArrow
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxlineshape')")
`K` ClearArrow

`##+K1 wxLineShape::ClearArrowsAtPosition`

`void ClearArrowsAtPosition(int position = -1)K`

Delete the arrows at the specified position, or at any position if *position* is -1.

`wxLineShape::ClearArrowsAtPosition`
`topic108`
`browse00154`
`K wxLineShape ClearArrowsAtPosition`
`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxlineshape')")`
`K ClearArrowsAtPosition`

`wxLineShape::DrawArrow`

`void DrawArrow(ArrowHead *arrow, double xOffset, bool proportionalOffset)`^K

Draws the given arrowhead (or annotation).

`wxLineShape::DrawArrow`

`topic109`

`browse00155`

`K wxLineShape DrawArrow`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxlineshape')")`

`K DrawArrow`

`$#+K!` **wxLineStyle::DeleteArrowHead**

bool DeleteArrowHead(long *arrowId*)^K

bool DeleteArrowHead(int *position*, const wxString& *name*)^K

Delete arrowhead by id or position and name.

`w`xLineStyle::DeleteArrowHead

`t`opic110

`b`rowse00156

`K` wxLineStyle DeleteArrowHead

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxlineshape')")

`K` DeleteArrowHead

`K` DeleteArrowHead

`$#+K!` wxLineShape::DeleteLineControlPoint

`bool DeleteLineControlPoint()`^K

Deletes an arbitrary point on the line.

^wxLineShape::DeleteLineControlPoint

^topic111

^browse00157

^K wxLineShape DeleteLineControlPoint

^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxlineshape')")

^K DeleteLineControlPoint

wxLineShape::DrawArrows

void DrawArrows(wxDC& dc)

Draws all arrows.

wxLineShape::DrawArrows
topic112
browse00158
K wxLineShape DrawArrows
E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxlineshape')")
K DrawArrows

wxLineShape::DrawRegion

void DrawRegion(wxDC& *dc*, wxShapeRegion **region*, double *x*, double *y*)^K

Format one region at this position.

^wxLineShape::DrawRegion

^topic113

^browse00159

^K wxLineShape DrawRegion

^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wlineshape')")

^K DrawRegion

`wxLineShape::EraseRegion`

`void EraseRegion(wxDC& dc, wxShapeRegion *region, double x, double y)`

Format one region at this position.

`wxLineShape::EraseRegion`

`topic114`

`browse00160`

`wxLineShape EraseRegion`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxlineshape')")`

`EraseRegion`

`$#+K!` **wxLineShape::FindArrowHead**

wxArrowHead * FindArrowHead(long arrowId)^K

wxArrowHead * FindArrowHead(int position, const wxString& name)^K

Find arrowhead by id or position and name.

`w`xLineShape::FindArrowHead

`t`opic115

`b`rowse00161

`K` wxLineShape FindArrowHead

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxlineshape')")

`K` FindArrowHead

`K` FindArrowHead

`$#+K!` wxLineShape::FindLineEndPoints

`void FindLineEndPoints(double *fromX, double *fromY, double *toX, double *toY)`^K

Finds the x, y points at the two ends of the line. This function can be used by e.g. line-routing routines to get the actual points on the two node images where the lines will be drawn to/from.

^wxLineShape::FindLineEndPoints

^topic116

^browse00162

^K wxLineShape FindLineEndPoints

^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxlineshape')")

^K FindLineEndPoints

`$#+K!` **wxLineShape::FindLinePosition**

int FindLinePosition(double x, double y)^K

Find which position we're talking about at this x, y. Returns
ARROW_POSITION_START, ARROW_POSITION_MIDDLE,
ARROW_POSITION_END.

`w` wxLineShape::FindLinePosition

`t`opic117

`b`rowse00163

`K` wxLineShape FindLinePosition

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxlineshape')")

`K` FindLinePosition

`$#+K!` **wxLineShape::FindMinimumWidth**

double FindMinimumWidth()^K

Finds the horizontal width for drawing a line with arrows in minimum space. Assume arrows at end only.

`w`xLineShape::FindMinimumWidth

`t`opic118

`b`rowse00164

`K` wxLineShape FindMinimumWidth

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxlineshape')")

`K` FindMinimumWidth

^{S#+K!}**wxLineShape::FindNth**

void FindNth(wxShape *image, int *nth, int *noArcs, bool incoming)^K

Finds the position of the line on the given object. Specify whether incoming or outgoing lines are being considered with *incoming*.

^wxLineShape::FindNth
^topic119
^browse00165
^K wxLineShape FindNth
^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxlineshape')")
^K FindNth

`wxLineShape::GetAttachmentFrom`

`int GetAttachmentFrom() const`

Returns the attachment point on the 'from' node.

`wxLineShape::GetAttachmentFrom`
`topic120`
`browse00166`
`K wxLineShape GetAttachmentFrom`
`K GetAttachmentFrom`
`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxlineshape')")`

`wxLineShape::GetAttachmentTo`

`int GetAttachmentTo() const`

Returns the attachment point on the 'to' node.

`wxLineShape::GetAttachmentTo`
`topic121`
`browse00167`
`K wxLineShape GetAttachmentTo`
`K GetAttachmentTo`
`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxlineshape')")`

`$#+K!` **wxLineShape::GetEnds**

void GetEnds(double *x1, double *y1, double *x2, double *y2)^K

Gets the visible endpoints of the lines for drawing between two objects.

`w`xLineShape::GetEnds
`t`opic122
`b`rowse00168
`K` wxLineShape GetEnds
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxlineshape')")
`K` GetEnds

`wxLineShape::GetFrom`

`wxShape * GetFrom() const`

Gets the 'from' object.

`wxLineShape::GetFrom`

`topic123`

`browse00169`

`wxLineShape GetFrom`

`GetFrom`

`enableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxlineshape')")`

`$#+K!` **wxLineShape::GetLabelPosition**

void GetLabelPosition(int *position*, double **x*, double **y*)^K

Get the reference point for a label. Region *x* and *y* are offsets from this. *position* is 0 (middle), 1 (start), 2 (end).

^wxLineShape::GetLabelPosition
^topic124
^browse00170
^K wxLineShape GetLabelPosition
^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxlineshape')")
^K GetLabelPosition

`$#+K!` wxLineShape::GetNextControlPoint

`wxPoint * GetNextControlPoint(wxShape *shape)`^K

Find the next control point in the line after the start/end point, depending on whether the shape is at the start or end.

`w`xLineShape::GetNextControlPoint
`t`opic125
`b`rowse00171
`K` wxLineShape GetNextControlPoint
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxlineshape')")
`K` GetNextControlPoint

`$#+K!` **wxLineStyle::GetTo**

wxShape * GetTo()^K

Gets the 'to' object.

^wxLineStyle::GetTo
^topic126
^browse00172
^K wxLineStyle GetTo
^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxlineshape')")
^K GetTo

`wxLineShape::Initialise`

`void Initialise()`

Initialises the line object.

`wxLineShape::Initialise`

`topic127`

`browse00173`

`wxLineShape Initialise`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxlineshape')")`

`Initialise`

`wxLineShape::InsertLineControlPoint`

`void InsertLineControlPoint()`^K

Inserts a control point at an arbitrary position.

`wxLineShape::InsertLineControlPoint`
topic128
browse00174
^K `wxLineShape InsertLineControlPoint`
^E `enableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxlineshape')")`
^K `InsertLineControlPoint`

`##+K! wxLineShape::IsEnd`

`bool IsEnd(wxShape *shape)K`

Returns TRUE if *shape* is at the end of the line.

`wxLineShape::IsEnd`

`topic129`

`browse00175`

`K wxLineShape IsEnd`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxlineshape')")`

`K IsEnd`

`wxLineShape::IsSpline`

`bool IsSpline()`

Returns TRUE if a spline is drawn through the control points, and FALSE otherwise.

`wxLineShape::IsSpline`
`topic130`
`browse00176`
`wxLineShape IsSpline`
`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxlineshape')")`
`IsSpline`

`$#+K!` **wxLineShape::MakeLineControlPoints**

void MakeLineControlPoints(int *n*)^K

Make a given number of control points (minimum of two).

`w`xLineShape::MakeLineControlPoints
`w`xlineshapemakelinecontrolpoints
`b`rowse00177
`K` wxLineShape MakeLineControlPoints
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxlineshape')")
`K` MakeLineControlPoints

`wxLineShape::OnMoveLink`

`void OnMoveLink(wxDC& dc, bool moveControlPoints = TRUE)`

Called when a connected object has moved, to move the link to correct position.

`wxLineShape::OnMoveLink`
topic131
browse00178
K wxLineShape OnMoveLink
E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxlineshape')")
K OnMoveLink

`##+K! wxLineShape::SetAttachmentFrom`

`void SetAttachmentTo(int fromAttach)K`

Sets the 'from' shape attachment.

`wxLineShape::SetAttachmentFrom`
`topic132`
`browse00179`
`K wxLineShape SetAttachmentFrom`
`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxlineshape')")`
`K SetAttachmentTo`

`$#+K!` **wxLineShape::SetAttachments**

void SetAttachments(int *fromAttach*, int *toAttach*)^K

Specifies which object attachment points should be used at each end of the line.

`w`xLineShape::SetAttachments

`t`opic133

`b`rowse00180

`K` wxLineShape SetAttachments

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxlineshape')")

`K` SetAttachments

`wxLineShape::SetAttachmentTo`

`void SetAttachmentTo(int toAttach)`

Sets the 'to' shape attachment.

`wxLineShape::SetAttachmentTo`
`topic134`
`browse00181`
`wxLineShape SetAttachmentTo`
`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxlineshape')")`
`SetAttachmentTo`

`wxLineShape::SetEnds`

`void SetEnds(double x1, double y1, double x2, double y2)`

Sets the end positions of the line.

`wxLineShape::SetEnds`
`topic135`
`browse00182`
`wxLineShape SetEnds`
`enableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxlineshape')")`
`SetEnds`

`wxLineShape::SetFrom`

`void SetFrom(wxShape *object)`

Sets the 'from' object for the line.

`wxLineShape::SetFrom`

`topic136`

`browse00183`

`wxLineShape SetFrom`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxlineshape')")`

`SetFrom`

`$#+K!` **wxLineShape::SetIgnoreOffsets**

void SetIgnoreOffsets(`bool ignore`)^K

Tells the shape whether to ignore offsets from the end of the line when drawing.

^wxLineShape::SetIgnoreOffsets

^topic137

^browse00184

^K wxLineShape SetIgnoreOffsets

^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxlineshape')")

^K SetIgnoreOffsets

`wxLineShape::SetSpline`

`void SetSpline(bool spline)`^K

Specifies whether a spline is to be drawn through the control points (TRUE), or a line (FALSE).

`wxLineShape::SetSpline`

`topic138`

`browse00185`

`K wxLineShape SetSpline`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxlineshape')")`

`K SetSpline`

`##+K! wxLineShape::SetTo`

`void SetTo(wxShape *object)K`

Sets the 'to' object for the line.

`wxLineShape::SetTo`

`topic139`

`browse00186`

`K wxLineShape SetTo`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxlineshape')")`

`K SetTo`

`wxLineShape::Straighten`

`void Straighten(wxDC* dc = NULL)`

Straighten verticals and horizontals. *dc* is optional.

`wxLineShape::Straighten`

`topic140`

`browse00187`

`wxLineShape Straighten`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxlineshape')")`

`Straighten`

`$#+K!` **wxLineShape::Unlink**

void Unlink()^K

Unlinks the line from the nodes at either end.

`w`xLineShape::Unlink
`t`opic141
`b`rowse00188
`K` wxLineShape Unlink
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxlineshape')")
`K` Unlink

`##+K! wxPolygonShape::wxPolygonShape`

`wxPolygonShape(void)K`

Constructor. Call [wxPolygonShape::Create](#) to specify the polygon's vertices.

```
wxPolygonShape::wxPolygonShape
topic142
browse00190
K wxPolygonShape wxPolygonShape
E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxpolygonshape')")
K wxPolygonShape
```

`$#+K! wxPolygonShape::~~wxPolygonShape`

`~wxPolygonShape()`^K

Destructor.

`wxPolygonShape::~~wxPolygonShape`

`topic143`

`browse00191`

`K wxPolygonShape ~wxPolygonShape`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxpolygonshape')")`

`K ~wxPolygonShape`

`$#+K!` **wxPolygonShape::Create**

void Create(wxList* points)^K

Takes a list of wxRealPoints; each point is an *offset* from the centre. The polygon's destructor will delete these points, so do not delete them yourself.

`w`xPolygonShape::Create
`w`xpolygonshapecreate
`b`rowse00192
`K` wxPolygonShape Create
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxpolygonshape')")
`K` Create

`##+K! wxPolygonShape::AddPolygonPoint`

`void AddPolygonPoint(int pos = 0)K`

Add a control point after the given point.

`wxPolygonShape::AddPolygonPoint`

`topic144`

`browse00193`

`K wxPolygonShape AddPolygonPoint`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxpolygonshape')")`

`K AddPolygonPoint`

`wxPolygonShape::CalculatePolygonCentre`

`void CalculatePolygonCentre()`

Recalculates the centre of the polygon.

`wxPolygonShape::CalculatePolygonCentre`

`topic145`

`browse00194`

`wxPolygonShape CalculatePolygonCentre`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxpolygonshape')")`

`CalculatePolygonCentre`

`wxPolygonShape::DeletePolygonPoint`

`void DeletePolygonPoint(int pos = 0)`

Deletes a control point.

`wxPolygonShape::DeletePolygonPoint`

`topic146`

`browse00195`

`wxPolygonShape DeletePolygonPoint`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxpolygonshape')")`

`DeletePolygonPoint`

`wxPolygonShape::GetPoints`

`wxList * GetPoints()`

Returns a pointer to the internal list of polygon vertices (wxRealPoints).

`wxPolygonShape::GetPoints`

`topic147`

`browse00196`

`wxPolygonShape GetPoints`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxpolygonshape')")`

`GetPoints`

`$#+K!` **wxPolygonShape::UpdateOriginalPoints**

void UpdateOriginalPoints()^K

If we've changed the shape, must make the original points match the working points with this function.

`w`xPolygonShape::UpdateOriginalPoints

`t`opic148

`b`rowse00197

`K` wxPolygonShape UpdateOriginalPoints

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxpolygonshape')")

`K` UpdateOriginalPoints

`wxRectangleShape::wxRectangleShape`

`wxRectangleShape(double width = 0.0, double height = 0.0)`^K

Constructor.

`wxRectangleShape::wxRectangleShape`

`topic149`

`browse00199`

`K wxRectangleShape wxRectangleShape`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxrectangleshape')")`

`K wxRectangleShape`

`wxRectangleShape::~wxRectangleShape`

`~wxRectangleShape()`^K

Destructor.

`wxRectangleShape::~wxRectangleShape`

`topic150`

`browse00200`

`K wxRectangleShape ~wxRectangleShape`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxrectangleshape')")`

`K ~wxRectangleShape`

`$#+K!` **wxRectangleShape::SetCornerRadius**

void SetCornerRadius(double *radius*)^K

Sets the radius of the rectangle's rounded corners. If the radius is zero, a non-rounded rectangle will be drawn. If the radius is negative, the value is the proportion of the smaller dimension of the rectangle.

`w`xRectangleShape::SetCornerRadius
`t`opic151
`b`rowse00201
`K` wxRectangleShape SetCornerRadius
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxrectangleshape')")
`K` SetCornerRadius

`##+K! wxShape::wxShape`

`wxShape(wxShapeCanvas* canvas = NULL)K`

Constructs a new wxShape.

`wxShape::wxShape`

`topic152`

`browse00204`

`K wxShape wxShape`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")`

`K wxShape`

`$#+K!` **wxShape::~~wxShape**

`~wxShape()`^K

Destructor.

`w`xShape::~~wxShape

`t`opic153

`b`rowse00205

`K` wxShape ~wxShape

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")

`K` ~wxShape

`wxShape::AddLine`

```
void AddLine(wxLineShape* line, wxShape* other, int attachFrom = 0, int attachTo = 0, int positionFrom = -1, int positionTo = -1)K
```

Adds a line between the specified canvas shapes, at the specified attachment points.

The position in the list of lines at each end can also be specified, so that the line will be drawn at a particular point on its attachment point.

`wxShape::AddLine`

`topic154`

`browse00206`

`wxShape AddLine`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshape')")`

`AddLine`

`$#+K!` **wxShape::AddRegion**

void AddRegion(wxShapeRegion* *region*)^K

Adds a region to the shape.

`w`xShape::AddRegion

`t`opic155

`b`rowse00207

`K` wxShape AddRegion

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshape')")

`K` AddRegion

`$#+K!` **wxShape::AddText**

void AddText(const wxString& *string*)^K

Adds a line of text to the shape's default text region.

`w` xShape::AddText

`t` opic156

`b` rowse00208

`K` wxShape AddText

`E` nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")

`K` AddText

`wxShape::AddToCanvas`

`void AddToCanvas(wxShapeCanvas* theCanvas, wxShape* addAfter=NULL)`^K

Adds the shape to the canvas's shape list. If *addAfter* is non-NULL, will add the shape after this one.

`wxShape::AddToCanvas`

`topic157`

`browse00209`

`K wxShape AddToCanvas`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")`

`K AddToCanvas`

`wxShape::AncestorSelected`

`bool AncestorSelected() const`

TRUE if the shape's ancestor is currently selected.

`wxShape::AncestorSelected`

`topic158`

`browse00210`

`K wxShape AncestorSelected`

`K AncestorSelected`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape`)")`

^{S#+K!}**wxShape::ApplyAttachmentOrdering**

void ApplyAttachmentOrdering(wxList& *linesToSort*)^K

Applies the line ordering in *linesToSort* to the shape, to reorder the way lines are attached.

^wxShape::ApplyAttachmentOrdering
^wxshapeapplyattachmentordering
^browse00211
^K wxShape ApplyAttachmentOrdering
^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")
^K ApplyAttachmentOrdering

`$#+K!` wxShape::AssignNewIds

`void AssignNewIds()`^K

Assigns new ids to this image and its children.

`w`xShape::AssignNewIds
`t`opic159
`b`rowse00212
`K` wxShape AssignNewIds
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")
`K` AssignNewIds

`wxShape::Attach`

`void Attach(wxShapeCanvas* can)`

Sets the shape's internal canvas pointer to point to the given canvas.

`wxShape::Attach`
`wxshapeattach`
`browse00213`
`wxShape Attach`
`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")`
`Attach`

`##+KKl wxShape::AttachmentIsValid`

`bool AttachmentIsValid(int attachment) const`

Returns TRUE if *attachment* is a valid attachment point.

`wxShape::AttachmentIsValid`

`wxshapeattachmentisvalid`

`rowse00214`

`K wxShape AttachmentIsValid`

`K AttachmentIsValid`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape`)")`

`$#+KKl wxShape::AttachmentSortTest`

bool AttachmentSortTest(int *attachment*, const wxRealPoint& *pt1*, const wxRealPoint& *pt2*) const

Returns TRUE if *pt1* is less than or equal to *pt2*, in the sense that one point comes before another on an edge of the shape. *attachment* is the attachment point (side) in question.

This function is used in [wxShape::MoveLineToNewAttachment](#) to determine the new line ordering.

`w_xShape::AttachmentSortTest
w_xshapeattachmentsorttest
b_rowse00215
K wxShape AttachmentSortTest
K AttachmentSortTest
E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape`)"`

`wxShape::CalcSimpleAttachment`

`wxRealPoint CalcSimpleAttachment(const wxRealPoint& pt1, const wxRealPoint& pt2, int nth, int noArcs, wxLineShape* line)`^K

Assuming the attachment lies along a vertical or horizontal line, calculates the position on that point.

Parameters

pt1

The first point of the line representing the edge of the shape.

pt2

The second point of the line representing the edge of the shape.

nth

The position on the edge (for example there may be 6 lines at this attachment point, and this may be the 2nd line).

noArcs

The number of lines at this edge.

line

The line shape.

Remarks

This function expects the line to be either vertical or horizontal, and determines which.

`wxShape::CalcSimpleAttachment`

`wxshapecalcsimpleattachment`

`rowse00216`

`wxShape CalcSimpleAttachment`

`enableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")`

`CalcSimpleAttachment`

`wxShape::CalculateSize`

`void CalculateSize()`

Called to calculate the shape's size if dependent on children sizes.

`wxShape::CalculateSize`

`topic160`

`browse00217`

`wxShape CalculateSize`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")`

`CalculateSize`

`wxShape::ClearAttachments`

`void ClearAttachments()`^K

Clears internal custom attachment point shapes (of class `wxAttachmentPoint`).

`wxShape::ClearAttachments`

`topic161`

`browse00218`

`wxShape ClearAttachments`

`enableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")`

`ClearAttachments`

`$#+K!` **wxShape::ClearRegions**

void ClearRegions()^K

Clears the wxShapeRegions from the shape.

`w`xShape::ClearRegions

`t`opic162

`b`rowse00219

`K` wxShape ClearRegions

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshape')")

`K` ClearRegions

`$#+K!` **wxShape::ClearText**

void ClearText(int *regionId* = 0)^K

Clears the text from the specified text region.

`w`xShape::ClearText

`t`opic163

`b`rowse00220

`K` wxShape ClearText

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshape')")

`K` ClearText

`$$$K! wxShape::Constrain`

`bool Constrain()`^K

Calculates the shape's constraints (if any). Applicable only to wxCompositeShape, does nothing if the shape is of a different class.

`wxShape::Constrain`
`topic164`
`browse00221`
`K wxShape Constrain`
`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")`
`K Constrain`

`$#+K!` **wxShape::Copy**

void Copy(wxShape& copy)^K

Copy this shape into *copy*. Every derived class must have one of these, and each Copy implementation must call the derived class's implementation to ensure everything is copied. See also [wxShape::CreateNewCopy](#).

`w`xShape::Copy
`w`xshapecopy
`b`rowse00222
`K` wxShape Copy
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")
`K` Copy

^{S#+K!}**wxShape::CreateNewCopy**

wxShape* **CreateNewCopy**(**bool** *resetMapping* = *TRUE*, **bool** *recompute* = *TRUE*)^K

Creates and returns a new copy of this shape (calling wxShape::Copy). Do not override this function.

This function should always be used to create a new copy, since it must do special processing for copying constraints associated with constraints.

If *resetMapping* is *TRUE*, a mapping table used for complex shapes is reset; this may not be desirable if the shape being copied is a child of a composite (and so the mapping table is in use).

If *recompute* is *TRUE*, wxShape::Recompute is called for the new shape.

Remarks

This function uses the wxWindows dynamic object creation system to create a new shape of the same type as 'this', before calling Copy.

If the event handler for this shape is not the same as the shape itself, the event handler is also copied using wxShapeEvtHandler::CreateNewCopy.

^wxShape::CreateNewCopy

^wxshapecreatenewcopy

^browse00223

^K wxShape CreateNewCopy

^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshape')")

^K CreateNewCopy

`wxShape::DeleteControlPoints`

`void DeleteControlPoints()`^K

Deletes the control points (or handles) for the shape. Does not redraw the shape.

`wxShape::DeleteControlPoints`

`topic165`

`browse00224`

`K wxShape DeleteControlPoints`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")`

`K DeleteControlPoints`

`wxShape::Detach`

`void Detach()`

Disassociates the shape from its canvas by setting the internal shape canvas pointer to NULL.

`wxShape::Detach`

`topic166`

`browse00225`

`K wxShape Detach`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")`

`K Detach`

`wxShape::Draggable`

`bool Draggable()`

TRUE if the shape may be dragged by the user.

`wxShape::Draggable`

`topic167`

`browse00226`

`wxShape Draggable`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")`

`Draggable`

`wxShape::Draw`

`void Draw(wxDC& dc)`

Draws the whole shape and any lines attached to it.

Do not override this function: override OnDraw, which is called by this function.

`wxShape::Draw`

`topic168`

`browse00227`

`wxShape Draw`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")`

`Draw`

`wxShape::DrawContents`

`void DrawContents(wxDC& dc)`

Draws the internal graphic of the shape (such as text).

Do not override this function: override `OnDrawContents`, which is called by this function.

`wxShape::DrawContents`

`topic169`

`browse00228`

`wxShape DrawContents`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")`

`DrawContents`

`wxShape::DrawLinks`

`void DrawLinks(wxDC& dc, int attachment = -1)`

Draws any lines linked to this shape.

`wxShape::DrawLinks`

`topic170`

`browse00229`

`wxShape DrawLinks`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")`

`DrawLinks`

wxShape::Erase

void Erase(wxDC& dc)

Erases the shape, but does not repair damage caused to other shapes.

wxShape::Erase

topic171

browse00230

K wxShape Erase

EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")

K Erase

`wxShape::EraseContents`

`void EraseContents(wxDC& dc)`^K

Erases the shape contents, that is, the area within the shape's minimum bounding box.

`wxShape::EraseContents`

`topic172`

`browse00231`

`K wxShape EraseContents`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")`

`K EraseContents`

`wxShape::EraseLinks`

`void EraseLinks(wxDC& dc, int attachment = -1)`

Erases links attached to this shape, but does not repair damage caused to other shapes.

`wxShape::EraseLinks`

`topic173`

`browse00232`

`wxShape EraseLinks`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")`

`EraseLinks`

`wxShape::FindRegion`

`wxShape * FindRegion(const wxString& regionName, int *regionId)K`

Finds the actual image ('this' if non-composite) and region id for the given region name.

`wxShape::FindRegion`

`topic174`

`browse00233`

`K wxShape FindRegion`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")`

`K FindRegion`

`$#+K!` **wxShape::FindRegionNames**

void FindRegionNames(wxStringList& *list*)^K

Finds all region names for this image (composite or simple). Supply an empty string list.

`w`xShape::FindRegionNames

`t`opic175

`b`rowse00234

`K` wxShape FindRegionNames

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshape')")

`K` FindRegionNames

`$#+K!` **wxShape::Flash**

void Flash()^K

Flashes the shape.

`w`xShape::Flash

`t`opic176

`b`rowse00235

`K` wxShape Flash

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")

`K` Flash

`$$$K! wxShape::FormatText`

`void FormatText(const wxString& s, int i = 0)`^K

Reformats the given text region; defaults to formatting the default region.

`w`xShape::FormatText

`t`opic177

`b`rowse00236

`K` wxShape FormatText

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")

`K` FormatText

`##+KK1 wxShape::GetAttachmentMode`

bool GetAttachmentMode() const

Returns the attachment mode, which is TRUE if attachments are used, FALSE otherwise (in which case lines will be drawn as if to the centre of the shape). See [wxShape::SetAttachmentMode](#).

wxShape::GetAttachmentMode
topic178
browse00237
K wxShape GetAttachmentMode
K GetAttachmentMode
E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape`)")

`$#+K!` **wxShape::GetAttachmentPosition**

bool GetAttachmentPosition(int *attachment*, double* *x*, double* *y*, int *nth* = 0, int *noArcs* = 1, wxLineStyle* *line* = NULL)^K

Gets the position at which the given attachment point should be drawn.

If *attachment* isn't found among the attachment points of the shape, returns FALSE.

^wxShape::GetAttachmentPosition

^wxshapegetattachmentposition

^browse00238

^K wxShape GetAttachmentPosition

^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshape')")

^K GetAttachmentPosition

`$#+K!` **wxShape::GetBoundingBoxMax**

void GetBoundingBoxMax(double *width, double *height)^K

Gets the maximum bounding box for the shape, taking into account external features such as shadows.

`w`xShape::GetBoundingBoxMax

`t`opic179

`b`rowse00239

`K` wxShape GetBoundingBoxMax

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshape')")

`K` GetBoundingBoxMax

`$#+K!` **wxShape::GetBoundingBoxMin**

void GetBoundingBoxMin(double *width, double *height)^K

Gets the minimum bounding box for the shape, that defines the area available for drawing the contents (such as text).

^wxShape::GetBoundingBoxMin

^topic180

^browse00240

^K wxShape GetBoundingBoxMin

^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshape')")

^K GetBoundingBoxMin

`$#+KKl wxShape::GetBrush`

`wxBrush* GetBrush() const`

Returns the brush used for filling the shape.

`wxShape::GetBrush`

`topic181`

`browse00241`

`K wxShape GetBrush`

`K GetBrush`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape`)")`

`wxShape::GetCanvas`

`wxShapeCanvas* GetCanvas() const`

Gets the internal canvas pointer.

`wxShape::GetCanvas`

topic182

browse00242

K wxShape GetCanvas

K GetCanvas

E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape`)")

`##+KK1 wxShape::GetCentreResize`

`bool GetCentreResize() const`

Returns TRUE if the shape is to be resized from the centre (the centre stands still), or FALSE if from the corner or side being dragged (the other corner or side stands still).

`w`xShape::GetCentreResize
`t`opic183
`b`rowse00243
`K` wxShape GetCentreResize
`K` GetCentreResize
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape`)")

`wxShape::GetChildren`

`wxList& GetChildren() const`

Returns a reference to the list of children for this shape.

`wxShape::GetChildren`

`topic184`

`browse00244`

`wxShape GetChildren`

`GetChildren`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape`)")`

`$#+K!` wxShape::GetClientData

`wxObject*` GetClientData()^K

Gets the client data associated with the shape (NULL if there is none).

`w`xShape::GetClientData

`t`opic185

`b`rowse00245

`K` wxShape GetClientData

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshape')")

`K` GetClientData

`wxShape::GetDisableLabel`

`bool GetDisableLabel() const`

Returns TRUE if the default region will not be shown, FALSE otherwise.

`wxShape::GetDisableLabel`
topic186
browse00246
K wxShape GetDisableLabel
K GetDisableLabel
E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape`)")

`wxShape::GetEventHandler`

`wxShapeEvtHandler* GetEventHandler() const`

Returns the event handler for this shape.

`wxShape::GetEventHandler`

`topic187`

`browse00247`

`K wxShape GetEventHandler`

`K GetEventHandler`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape`)")`

`wxShape::GetFixedHeight`

`bool GetFixedHeight() const`

Returns TRUE if the shape cannot be resized in the vertical plane.

`wxShape::GetFixedHeight`

`topic188`

`browse00248`

`K wxShape GetFixedHeight`

`K GetFixedHeight`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape`)")`

`$#+K!` **wxShape::GetFixedSize**

void GetFixedSize(bool * x, bool * y)^K

Returns flags indicating whether the shape is of fixed size in either direction.

`w`xShape::GetFixedSize

`t`opic189

`b`rowse00249

`K` wxShape GetFixedSize

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshape')")

`K` GetFixedSize

`wxShape::GetFixedWidth`

`bool GetFixedWidth() const`

Returns TRUE if the shape cannot be resized in the horizontal plane.

`wxShape::GetFixedWidth`

`topic190`

`browse00250`

`K wxShape GetFixedWidth`

`K GetFixedWidth`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape`)"`

`wxShape::GetFont`

`wxFont* GetFont(int regionId = 0) const`

Gets the font for the specified text region.

`wxShape::GetFont`

`topic191`

`browse00251`

`wxShape GetFont`

`GetFont`

`enableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")`

`$#+KKl` **wxShape::GetFunc**

wxString GetFunc() const

Gets a string representing the type of the shape, to be used when writing out shape descriptions to a file. This is overridden by each derived shape class to provide an appropriate type string. By default, "node_image" is used for non-line shapes, and "arc_image" for lines.

`w`xShape::GetFunc
`t`opic192
`b`rowse00252
`K` wxShape GetFunc
`K` GetFunc
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape`)")

`$#+KKl wxShape::GetId`

long GetId() const

Returns the integer identifier for this shape.

`w_xShape::GetId`
`topic193`
`browse00253`
`K wxShape GetId`
`K GetId`
`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape`)")`

`$#+K!` wxShape::GetLinePosition

`int GetLinePosition(wxLineShape* line)K`

Gets the zero-based position of *line* in the list of lines for this shape.

`w`xShape::GetLinePosition

`w`xshapegetlineposition

`b`rowse00254

`K` wxShape GetLinePosition

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshape')")

`K` GetLinePosition

`$#+KKl wxShape::GetLines`

`wxList& GetLines() const`

Returns a reference to the list of lines connected to this shape.

`wxShape::GetLines`

`topic194`

`browse00255`

`K wxShape GetLines`

`K GetLines`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")`

`wxShape::GetMaintainAspectRatio`

`bool GetMaintainAspectRatio() const`

If returns TRUE, resizing the shape will not change the aspect ratio (width and height will be in the original proportion).

`wxShape::GetMaintainAspectRatio`
`wxshapegetmaintainaspectratio`
`rowse00256`
`wxShape GetMaintainAspectRatio`
`GetMaintainAspectRatio`
`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')`

`##+KKl wxShape::GetNumberOfAttachments`

`int GetNumberOfAttachments() const`

Gets the number of attachment points for this shape.

`w_xShape::GetNumberOfAttachments`
`w_xshapegetnumberofattachments`
`rowse00257`
`K wxShape GetNumberOfAttachments`
`K GetNumberOfAttachments`
`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")`

`##+KK1 wxShape::GetNumberOfTextRegions`

`int GetNumberOfTextRegions() const`

Gets the number of text regions for this shape.

`w`xShape::GetNumberOfTextRegions
`t`opic195
`b`rowse00258
`K` wxShape GetNumberOfTextRegions
`K` GetNumberOfTextRegions
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape`)")

`wxShape::GetParent`

`wxShape * GetParent() const`

Returns the parent of this shape, if it is part of a composite.

`wxShape::GetParent`

`topic196`

`browse00259`

`K wxShape GetParent`

`K GetParent`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")`

`wxShape::GetPen`

`wxPen* GetPen() const`

Returns the pen used for drawing the shape's outline.

`wxShape::GetPen`

`topic197`

`browse00260`

`K wxShape GetPen`

`K GetPen`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape`)")`

`$#+K!` **wxShape::GetPerimeterPoint**

bool GetPerimeterPoint(double x1, double y1, double x2, double y2, double *x3, double *y3)^K

Gets the point at which the line from (x1, y1) to (x2, y2) hits the shape. Returns TRUE if the line hits the perimeter.

`w`xShape::GetPerimeterPoint
`t`opic198
`b`rowse00261
`K` wxShape GetPerimeterPoint
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshape')")
`K` GetPerimeterPoint

`$#+K!` **wxShape::GetRegionId**

int GetRegionId(const wxString& name)^K

Gets the region's identifier by name. This is *not* unique for within an entire composite, but is unique for the image.

`w`xShape::GetRegionId
`g`etregionid
`b`rowse00262
`K` wxShape GetRegionId
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")
`K` GetRegionId

`$#+K!` wxShape::GetRegionName

wxString GetRegionName(int *regionId* = 0)^K

Gets the region's name. A region's name can be used to uniquely determine a region within an entire composite image hierarchy. See also [wxShape::SetRegionName](#).

`w`xShape::GetRegionName
`g`etregionname
`b`rowse00263
`K` wxShape GetRegionName
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")
`K` GetRegionName

`$#+K!` wxShape::GetRegions

`wxList& GetRegions()`^K

Returns the list of wxShapeRegions.

`w`xShape::GetRegions

`g`etregions

`b`rowse00264

`K` wxShape GetRegions

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshape')")

`K` GetRegions

`wxShape::GetRotation`

`double GetRotation() const`

Returns the angle of rotation in radians.

`wxShape::GetRotation`

`topic199`

`browse00265`

`K wxShape GetRotation`

`K GetRotation`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape`)")`

`wxShape::GetSensitivityFilter`

`void GetSensitivityFilter() const`

Returns the sensitivity filter, a bitlist of values. See [wxShape::SetSensitivityFilter](#).

`wxShape::GetSensitivityFilter`

`topic200`

`browse00266`

`K wxShape GetSensitivityFilter`

`K GetSensitivityFilter`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape`)"`

`wxShape::GetShadowMode`

`int SetShadowMode() const`

Returns the shadow mode. See [wxShape::SetShadowMode](#).

`wxShape::GetShadowMode`

`topic201`

`browse00267`

`K wxShape GetShadowMode`

`K SetShadowMode`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")`

`##+KK1 wxShape::GetSpaceAttachments`

`bool GetSpaceAttachments() const`

Indicates whether lines should be spaced out evenly at the point they touch the node (TRUE), or whether they should join at a single point (FALSE).

`wxShape::GetSpaceAttachments`

`topic202`

`browse00268`

`K wxShape GetSpaceAttachments`

`K GetSpaceAttachments`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape`)"`

`##+KK1 wxShape::GetTextColour`

`wxString GetTextColour(int regionId = 0) const`

Gets the colour for the specified text region.

`wxShape::GetTextColour`

`topic203`

`browse00269`

`K wxShape GetTextColour`

`K GetTextColour`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape`)")`

`wxShape::GetTopAncestor`

`wxShape * GetTopAncestor() const`

Returns the top-most ancestor of this shape (the root of the composite).

`wxShape::GetTopAncestor`

`topic204`

`browse00270`

`wxShape GetTopAncestor`

`GetTopAncestor`

`enableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape`)")`

`wxShape::GetX`

`double GetX() const`

Gets the x position of the centre of the shape.

`wxShape::GetX`

`topic205`

`browse00271`

`K wxShape GetX`

`K GetX`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape`)")`

`wxShape::GetY`

`double GetY() const`

Gets the y position of the centre of the shape.

`wxShape::GetY`

`topic206`

`browse00272`

`K wxShape GetY`

`K GetY`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape`)")`

`$#+K!` **wxShape::HitTest**

bool HitTest(double x, double y, int* attachment, double* distance)^K

Given a point on a canvas, returns TRUE if the point was on the shape, and returns the nearest attachment point and distance from the given point and target.

`w` wxShape::HitTest

`t`opic207

`b`rowse00273

`K` wxShape HitTest

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshape')")

`K` HitTest

wxShape::Insert

void InsertInCanvas(wxShapeCanvas* canvas)^K

Inserts the shape at the front of the shape list of *canvas*.

^wxShape::Insert

^topic208

^browse00274

^K wxShape Insert

^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")

^K InsertInCanvas

`##+KK1 wxShape::IsHighlighted`

`bool IsHighlighted() const`

Returns TRUE if the shape is highlighted. Shape highlighting is unimplemented.

`wxShape::IsHighlighted`

`topic209`

`browse00275`

`K wxShape IsHighlighted`

`K IsHighlighted`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape`)")`

`##+KKl wxShape::IsShown`

bool IsShown() const

Returns TRUE if the shape is in a visible state, FALSE otherwise. Note that this has nothing to do with whether the window is hidden or the shape has scrolled off the canvas; it refers to the internal visibility flag.

`wxShape::IsShown`

`topic210`

`browse00276`

`K wxShape IsShown`

`K IsShown`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape`)")`

`$#+K!` **wxShape::MakeControlPoints**

void MakeControlPoints()^K

Make a list of control points (draggable handles) appropriate to the shape.

^wxShape::MakeControlPoints

^topic211

^browse00277

^K wxShape MakeControlPoints

^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshape')")

^K MakeControlPoints

`$#+K!` **wxShape::MakeMandatoryControlPoints**

void MakeMandatoryControlPoints()^K

Make the mandatory control points. For example, the control point on a dividing line should appear even if the divided rectangle shape's handles should not appear (because it is the child of a composite, and children are not resizable).

`w`xShape::MakeMandatoryControlPoints
`t`opic212
`b`rowse00278
`K` wxShape MakeMandatoryControlPoints
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")
`K` MakeMandatoryControlPoints

^{S#+K!}**wxShape::Move**

void Move(wxDC& dc, double x1, double y1, bool display = TRUE)^K

Move the shape to the given position, redrawing if *display* is TRUE.

^wxShape::Move
^wxshapemove
^browse00279
^K wxShape Move
^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshape')")
^K Move

^{S#+K!} **wxShape::MoveLineToNewAttachment**

void MoveLineToNewAttachment(wxDC& dc, wxLineShape* toMove, double x, double y)^K

Move the given line (which must already be attached to the shape) to a different attachment point on the shape, or a different order on the same attachment.

Cals wxShape::AttachmentSortTest and then wxShapeEvtHandler::OnChangeAttachment.

^wxShape::MoveLineToNewAttachment
^wxshapemovelinetonewattachment
^browse00280
^K wxShape MoveLineToNewAttachment
^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")
^K MoveLineToNewAttachment

wxShape::MoveLinks

void MoveLinks(wxDC& dc)

Redraw all the lines attached to the shape.

wxShape::MoveLinks

topic213

browse00281

wxShape MoveLinks

enableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")

MoveLinks

`$#+K!` **wxShape::NameRegions**

void NameRegions(const wxString& *parentName* = "")^K

Make unique names for all the regions in a shape or composite shape.

^wxShape::NameRegions

^topic214

^browse00282

^K wxShape NameRegions

^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshape')")

^K NameRegions

`$#+K!` **wxShape::Rotate**

void Rotate(double x, double y, double theta)^K

Rotate about the given axis by the given amount in radians (does nothing for most shapes). But even non-rotating shapes should record their notional rotation in case it's important (e.g. in dog-leg code).

`w`xShape::Rotate
`t`opic215
`b`rowse00283
`K` wxShape Rotate
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshape')")
`K` Rotate

`$$$K! wxShape::ReadConstraints`

`void ReadConstraints(wxExpr *clause, wxExprDatabase *database)K`

If the shape is a composite, it may have constraints that need to be read in a separate pass.

`wxShape::ReadConstraints`

`topic216`

`browse00284`

`K wxShape ReadConstraints`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")`

`K ReadConstraints`

^{S#+K!}**wxShape::ReadAttributes**

void ReadAttributes(wxExpr* *clause*)^K

Reads the attributes (data member values) from the given expression.

^wxShape::ReadAttributes

^topic217

^browse00285

^K wxShape ReadAttributes

^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshape')")

^K ReadAttributes

`wxShape::ReadRegions`

`void ReadRegions(wxExpr *clause)K`

Reads in the regions.

`wxShape::ReadRegions`

`topic218`

`browse00286`

`K wxShape ReadRegions`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")`

`K ReadRegions`

`$#+K!` **wxShape::Recentre**

void Recentre()^K

Does recentring (or other formatting) for all the text regions for this shape.

^wxShape::Recentre

^topic219

^browse00287

^K wxShape Recentre

^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshape')")

^K Recentre

`$#+K!` **wxShape::RemoveFromCanvas**

void RemoveFromCanvas(wxShapeCanvas* canvas)^K

Removes the shape from the canvas.

`w`xShape::RemoveFromCanvas

`t`opic220

`b`rowse00288

`K` wxShape RemoveFromCanvas

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshape')")

`K` RemoveFromCanvas

`wxShape::ResetControlPoints`

`void ResetControlPoints()`

Resets the positions of the control points (for instance when the shape's shape has changed).

`wxShape::ResetControlPoints`

`topic221`

`browse00289`

`wxShape ResetControlPoints`

`enableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")`

`ResetControlPoints`

`wxShape::ResetMandatoryControlPoints`

`void ResetMandatoryControlPoints()`^K

Reset the mandatory control points. For example, the control point on a dividing line should appear even if the divided rectangle shape's handles should not appear (because it is the child of a composite, and children are not resizable).

^w`wxShape::ResetMandatoryControlPoints`
^t`opic222`
^b`rowse00290`
^K `wxShape ResetMandatoryControlPoints`
^E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")`
^K `ResetMandatoryControlPoints`

`$#+K!` **wxShape::Recompute**

bool Recompute()^K

Recomputes any constraints associated with the shape (normally applicable to wxCompositeShapes only, but harmless for other classes of shape).

`w`xShape::Recompute
`w`xshaperecompute
`b`rowse00291
`K` wxShape Recompute
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")
`K` Recompute

`wxShape::RemoveLine`

`void RemoveLine(wxLineShape* line)`^K

Removes the given line from the shape's list of attached lines.

`wxShape::RemoveLine`
topic223
browse00292
K wxShape RemoveLine
E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")
K RemoveLine

`$#+K!` **wxShape::Select**

void Select(**bool** *select* = *TRUE*)^K

Selects or deselects the given shape, drawing or erasing control points (handles) as necessary.

^wxShape::Select
^wxshapeselect
^browse00293
^K wxShape Select
^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshape')")
^K Select

`$#+KKl wxShape::Selected`

`bool Selected() const`

TRUE if the shape is currently selected.

`w_xShape::Selected`

`w_xshapeselected`

`browse00294`

`K wxShape Selected`

`K Selected`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape`)")`

`$#+K!` **wxShape::SetAttachmentMode**

void SetAttachmentMode(*bool flag*)^K

Sets the attachment mode to TRUE or FALSE. If TRUE, attachment points will be significant when drawing lines to and from this shape. If FALSE, lines will be drawn as if to the centre of the shape.

`w`xShape::SetAttachmentMode
`w`xshap esetattachmentmode
`b`rowse00295
`K` wxShape SetAttachmentMode
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")
`K` SetAttachmentMode

`wxShape::SetBrush`

`void SetBrush(wxBrush *brush)`

Sets the brush for filling the shape's shape.

`wxShape::SetBrush`

`topic224`

`browse00296`

`wxShape SetBrush`

`enableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")`

`SetBrush`

`$#+K!` **wxShape::SetCanvas**

void SetCanvas(wxShapeCanvas* *theCanvas*)^K

Identical to wxShape::Attach.

`w`xShape::SetCanvas

`w`xshapetocanvas

`b`rowse00297

`K` wxShape SetCanvas

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshape')")

`K` SetCanvas

`wxShape::SetCentreResize`

`void SetCentreResize(bool cr)`

Specify whether the shape is to be resized from the centre (the centre stands still) or from the corner or side being dragged (the other corner or side stands still).

`wxShape::SetCentreResize`
topic225
browse00298
K wxShape SetCentreResize
E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")
K SetCentreResize

`$#+K!` **wxShape::SetClientData**

void SetClientData(wxObject *clientData)^K

Sets the client data.

`w`xShape::SetClientData

`t`opic226

`b`rowse00299

`K` wxShape SetClientData

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")

`K` SetClientData

`$#+K!` **wxShape::SetDefaultRegionSize**

void SetDefaultRegionSize()^K

Set the default region to be consistent with the shape size.

`w`xShape::SetDefaultRegionSize
`s`etdefaultregionsize
`b`rowse00300
`K` wxShape SetDefaultRegionSize
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshape')")
`K` SetDefaultRegionSize

`wxShape::SetDisableLabel`

`void SetDisableLabel(bool flag)`

Set *flag* to TRUE to stop the default region being shown, FALSE otherwise.

`wxShape::SetDisableLabel`

`topic227`

`browse00301`

`wxShape SetDisableLabel`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")`

`SetDisableLabel`

`wxShape::SetDraggable`

`void SetDraggable(bool drag, bool recursive = FALSE)`

Sets the shape to be draggable or not draggable.

`wxShape::SetDraggable`

`topic228`

`browse00302`

`wxShape SetDraggable`

`enableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")`

`SetDraggable`

\$\$\$K! wxShape::SetDrawHandles

void SetDrawHandles(bool *drawH*)^K

Sets the *drawHandles* flag for this shape and all descendants. If *drawH* is TRUE (the default), any handles (control points) will be drawn. Otherwise, the handles will not be drawn.

wxShape::SetDrawHandles

topic229

browse00303

K wxShape SetDrawHandles

EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshape')")

K SetDrawHandles

`wxShape::SetEventHandler`

`void GetEventHandler(wxShapeEvtHandler *handler)`

Sets the event handler for this shape.

`wxShape::SetEventHandler`

`topic230`

`browse00304`

`K wxShape SetEventHandler`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshape')")`

`K GetEventHandler`

`wxShape::SetFixedSize`

`void SetFixedSize(bool x, bool y)`

Sets the shape to be of the given, fixed size.

`wxShape::SetFixedSize`

`topic231`

`browse00305`

`wxShape SetFixedSize`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")`

`SetFixedSize`

`wxShape::SetFont`

`void SetFont(wxFont *font, int regionId = 0)`

Sets the font for the specified text region.

`wxShape::SetFont`

`topic232`

`browse00306`

`wxShape SetFont`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")`

`SetFont`

^{S#+K!}**wxShape::SetFormatMode**

void SetFormatMode(int mode, int regionId = 0)^K

Sets the format mode of the default text region. The argument can be a bit list of the following:

FORMAT_NONE No formatting.

FORMAT_CENTRE_HORIZ Horizontal centring.

FORMAT_CENTRE_VERT Vertical centring.

^wwxShape::SetFormatMode

^setformatmode

^browse00307

^KwxShape SetFormatMode

^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshape')")

^KSetFormatMode

`$$$K! wxShape::SetHighlight`

`void SetHighlight(bool hi, bool recurse = FALSE)K`

Sets the highlight for a shape. Shape highlighting is unimplemented.

`w_xShape::SetHighlight`
`topic233`
`browse00308`
`K wxShape SetHighlight`
`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")`
`K SetHighlight`

`wxShape::SetId`

`void SetId(long id)`

Set the integer identifier for this shape.

`wxShape::SetId`

`topic234`

`browse00309`

`wxShape SetId`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")`

`SetId`

`$#+K!` **wxShape::SetMaintainAspectRatio**

void SetMaintainAspectRatio(bool *flag*)^K

If the argument is TRUE, tells the shape that resizes should not change the aspect ratio (width and height should be in the original proportion).

`w`xShape::SetMaintainAspectRatio
`w`xshapetomaintainaspectratio
`b`rowse00310
`K` wxShape SetMaintainAspectRatio
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")
`K` SetMaintainAspectRatio

`$#+K!` **wxShape::SetPen**

void SetPen(wxPen *pen)^K

Sets the pen for drawing the shape's outline.

`w`xShape::SetPen

`t`opic235

`b`rowse00311

`K` wxShape SetPen

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshape')")

`K` SetPen

`$#+K!` **wxShape::SetRegionName**

void SetRegionName(const wxString& name, int regionId = 0)^K

Sets the name for this region. The name for a region is unique within the scope of the whole composite, whereas a region id is unique only for a single image.

`w`xShape::SetRegionName
`w`xshapetregionname
`b`rowse00312
`K` wxShape SetRegionName
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")
`K` SetRegionName

^{S#+K!}**wxShape::SetSensitivityFilter**

void SetSensitivityFilter(int *sens=OP_ALL*, bool *recursive = FALSE*)^K

Sets the shape to be sensitive or insensitive to specific mouse operations.

sens is a bitlist of the following:

{bmc bullet.bmp} OP_CLICK_LEFT

{bmc bullet.bmp} OP_CLICK_RIGHT

{bmc bullet.bmp} OP_DRAG_LEFT

{bmc bullet.bmp} OP_DRAG_RIGHT

{bmc bullet.bmp} OP_ALL (equivalent to a combination of all the above).

^wwxShape::SetSensitivityFilter

^wwxshapetsensitivityfilter

^browse00313

^KwxShape SetSensitivityFilter

^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshape')")

^KSetSensitivityFilter

^{S#+K!}**wxShape::SetShadowMode**

void SetShadowMode(int mode, bool redraw = FALSE)^K

Sets the shadow mode (whether a shadow is drawn or not). *mode* can be one of the following:

SHADOW_NONE No shadow (the default).

SHADOW_LEFT Shadow on the left side.

SHADOW_RIGHT Shadow on the right side.

^wxShape::SetShadowMode
^wxshapeshadowmode
^browse00314
^K wxShape SetShadowMode
^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")
^K SetShadowMode

`$#+K!` **wxShape::SetSize**

void SetSize(double x, double y, bool recursive = TRUE)^K

Sets the shape's size.

^wxShape::SetSize

^topic236

^browse00315

^K wxShape SetSize

^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshape')")

^K SetSize

`$#+K!` **wxShape::SetSpaceAttachments**

void SetSpaceAttachments(bool *sp*)^K

Indicate whether lines should be spaced out evenly at the point they touch the node (TRUE), or whether they should join at a single point (FALSE).

^wxShape::SetSpaceAttachments

^topic237

^browse00316

^K wxShape SetSpaceAttachments

^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshape')")

^K SetSpaceAttachments

`wxShape::SetTextColour`

`void SetTextColour(const wxString& colour, int regionId = 0)`

Sets the colour for the specified text region.

`wxShape::SetTextColour`

`topic238`

`browse00317`

`wxShape SetTextColour`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshape')")`

`SetTextColour`

`wxShape::SetX`

`void SetX(double x)`

Sets the x position of the shape.

`wxShape::SetX`

`topic239`

`browse00318`

`wxShape SetX`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")`

`SetX`

`wxShape::SetX`

`void SetY(double y)`

Sets the *y* position of the shape.

`wxShape::SetX`

`topic240`

`browse00319`

`K wxShape SetX`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")`

`K SetY`

`$#+K!` **wxShape::SpaceAttachments**

void SpaceAttachments(bool *sp*)^K

Sets the spacing mode: if TRUE, lines at the same attachment point will be spaced evenly across that side of the shape. If false, all lines at the same attachment point will emanate from the same point.

`w`xShape::SpaceAttachments

`t`opic241

`b`rowse00320

`K` wxShape SpaceAttachments

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshape')")

`K` SpaceAttachments

`$#+K!` **wxShape::Show**

void Show(**bool** *show*)^K

Sets a flag indicating whether the shape should be drawn.

^wxShape::Show

^topic242

^browse00321

^K wxShape Show

^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshape')")

^K Show

`$#+K!` **wxShape::Unlink**

void Unlink()^K

If the shape is a line, unlinks the nodes attached to the shape, removing itself from the list of lines for each of the 'to' and 'from' nodes.

`w`xShape::Unlink
`t`opic243
`b`rowse00322
`K` wxShape Unlink
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")
`K` Unlink

`wxShape::WriteAttributes`

`void WriteAttributes(wxExpr *clause)`^K

Writes the shape's attributes (data member values) into the given expression.

`wxShape::WriteAttributes`

`topic244`

`browse00323`

`wxShape WriteAttributes`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshape')")`

`WriteAttributes`

`$#+K!` **wxShape::WriteRegions**

void WriteRegions(wxExpr **clause*)^K

Writes the regions.

`w`xShape::WriteRegions

`t`opic245

`b`rowse00324

`K` wxShape WriteRegions

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshape')")

`K` WriteRegions

`$#+K!` **wxShapeCanvas::wxShapeCanvas**

wxShapeCanvas(**wxWindow*** *parent* = *NULL*, **wxWindowID** *id* = *-1*, **const wxPoint&** *pos* = *wxDefaultPosition*, **const wxSize&** *size* = *wxDefaultSize*, **long** *style* = *wxBORDER*)^K

Constructor.

`w` xShapeCanvas::wxShapeCanvas

`t` opic246

`b` rowse00326

`K` wxShapeCanvas wxShapeCanvas

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshapecanvas')")

`K` wxShapeCanvas

`$#+K! wxShapeCanvas::~~wxShapeCanvas`

`~wxShapeCanvas()K`

Destructor.

`wxShapeCanvas::~~wxShapeCanvas`

`topic247`

`browse00327`

`K wxShapeCanvas ~wxShapeCanvas`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshapecanvas')")`

`K ~wxShapeCanvas`

`$#+K!` **wxShapeCanvas::AddShape**

void AddShape(wxShape *shape, wxShape *addAfter = NULL)^K

Adds a shape to the diagram. If *addAfter* is non-NULL, the shape will be added after this one.

`w`xShapeCanvas::AddShape
`t`opic248
`b`rowse00328
`K` wxShapeCanvas AddShape
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshapecanvas')")
`K` AddShape

`wxShapeCanvas::FindShape`

`wxShape * FindShape(double x1, double y, int *attachment, wxClassInfo *info = NULL, wxShape *notImage = NULL)`^K

Find a shape under this mouse click. Returns the shape (or NULL), and the nearest attachment point.

If *info* is non-NULL, a shape whose class which is a descendant of the desired class is found.

If *notImage* is non-NULL, shapes which are descendants of *notImage* are ignored.

`wxShapeCanvas::FindShape`
topic249
browse00329
K wxShapeCanvas FindShape
E nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshapecanvas')")
K FindShape

^{S#+K!}**wxShapeCanvas::FindFirstSensitiveShape**

wxShape * FindFirstSensitiveShape(double x1, double y, int *attachment, int op)^K

Finds the first sensitive shape whose sensitivity filter matches *op*, working up the hierarchy of composites until one (or none) is found.

^wxShapeCanvas::FindFirstSensitiveShape
^topic250
^browse00330
^K wxShapeCanvas FindFirstSensitiveShape
^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshapecanvas')")
^K FindFirstSensitiveShape

`##+KK1 wxShapeCanvas::GetDiagram`

`wxDiagram* GetDiagram() const`

Returns the canvas associated with this diagram.

`wxShapeCanvas::GetDiagram`

`topic251`

`browse00331`

`K wxShapeCanvas GetDiagram`

`K GetDiagram`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshapecanvas')")`

`##+KK1 wxShapeCanvas::GetGridSpacing`

`double GetGridSpacing() const`

Returns the grid spacing.

`w`xShapeCanvas::GetGridSpacing
`t`opic252
`b`rowse00332
`K` wxShapeCanvas GetGridSpacing
`K` GetGridSpacing
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshapecanvas')")

`##+KK1 wxShapeCanvas::GetMouseTolerance`

`int GetMouseTolerance() const`

Returns the tolerance within which a mouse move is ignored.

`w`xShapeCanvas::GetMouseTolerance
`t`opic253
`b`rowse00333
`K` wxShapeCanvas GetMouseTolerance
`K` GetMouseTolerance
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshapecanvas')")

`##+KK1 wxShapeCanvas::GetShapeList`

`wxList* GetShapeList() const`

Returns a pointer to the internal shape list.

`wxShapeCanvas::GetShapeList`

`topic254`

`browse00334`

`K wxShapeCanvas GetShapeList`

`K GetShapeList`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshapecanvas')")`

`##+KKl wxShapeCanvas::GetQuickEditMode`

`bool GetQuickEditMode() const`

Returns quick edit mode for the associated diagram.

`w`xShapeCanvas::GetQuickEditMode
`t`opic255
`b`rowse00335
`K` wxShapeCanvas GetQuickEditMode
`K` GetQuickEditMode
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshapecanvas')")

`wxShapeCanvas::InsertShape`

`void InsertShape(wxShape* shape)`

Inserts a shape at the front of the shape list.

`wxShapeCanvas::InsertShape`

`topic256`

`browse00336`

`wxShapeCanvas InsertShape`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshapecanvas')")`

`InsertShape`

`$#+K!` **wxShapeCanvas::OnBeginDragLeft**

void OnBeginDragLeft(double x, double y, int keys = 0)^K

Called when the start of a left-button drag event on the canvas background is detected by `OnEvent`. You may override this member; by default it does nothing.

`keys` is a bit list of the following:

{bmc bullet.bmp} `KEY_SHIFT`

{bmc bullet.bmp} `KEY_CTRL`

See also [wxShapeCanvas::OnDragLeft](#), [wxShapeCanvas::OnEndDragLeft](#).

^wwxShapeCanvas::OnBeginDragLeft

^wwxshapecanvasonbegindragleft

^browse00337

^KwxShapeCanvas OnBeginDragLeft

^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshapecanvas')")

^K OnBeginDragLeft

`$#+K!` **wxShapeCanvas::OnBeginDragRight**

void OnBeginDragRight(double x, double y, int keys = 0)^K

Called when the start of a right-button drag event on the canvas background is detected by `OnEvent`. You may override this member; by default it does nothing.

keys is a bit list of the following:

{bmc bullet.bmp} KEY_SHIFT

{bmc bullet.bmp} KEY_CTRL

See also [wxShapeCanvas::OnDragRight](#), [wxShapeCanvas::OnEndDragRight](#).

^wwxShapeCanvas::OnBeginDragRight

^wwxshapecanvasonbegindragright

^browse00338

^KwxShapeCanvas OnBeginDragRight

^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshapecanvas')")

^K OnBeginDragRight

`$#+K!` **wxShapeCanvas::OnEndDragLeft**

void OnEndDragLeft(double x, double y, int keys = 0)^K

Called when the end of a left-button drag event on the canvas background is detected by `OnEvent`. You may override this member; by default it does nothing.

`keys` is a bit list of the following:

{bmc bullet.bmp} `KEY_SHIFT`

{bmc bullet.bmp} `KEY_CTRL`

See also [wxShapeCanvas::OnDragLeft](#), [wxShapeCanvas::OnBeginDragLeft](#).

`w` wxShapeCanvas::OnEndDragLeft

`w` wxshapecanvasonenddragleft

`b` rowse00339

`K` wxShapeCanvas OnEndDragLeft

`E` nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshapecanvas')")

`K` OnEndDragLeft

`wxShapeCanvas::OnEndDragRight`

`void OnEndDragRight(double x, double y, int keys = 0)`^K

Called when the end of a right-button drag event on the canvas background is detected by `OnEvent`. You may override this member; by default it does nothing.

`keys` is a bit list of the following:

{bmc bullet.bmp} `KEY_SHIFT`

{bmc bullet.bmp} `KEY_CTRL`

See also [`wxShapeCanvas::OnDragRight`](#), [`wxShapeCanvas::OnBeginDragRight`](#).

^w`wxShapeCanvas::OnEndDragRight`
^w`wxshapecanvasonenddragright`
^b`rowse00340`
^K `wxShapeCanvas OnEndDragRight`
^E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshapecanvas')")`
^K `OnEndDragRight`

§#+K! **wxShapeCanvas::OnDragLeft**

void OnDragLeft(bool *draw*, double *x*, double *y*, int *keys* = 0)^K

Called when a left-button drag event on the canvas background is detected by OnEvent. You may override this member; by default it does nothing.

draw is alternately TRUE and FALSE, to assist drawing and erasing.

keys is a bit list of the following:

{bmc bullet.bmp} KEY_SHIFT

{bmc bullet.bmp} KEY_CTRL

See also [wxShapeCanvas::OnBeginDragLeft](#), [wxShapeCanvas::OnEndDragLeft](#).

^w wxShapeCanvas::OnDragLeft

^w wxshapecanvasondragleft

^b rowse00341

^K wxShapeCanvas OnDragLeft

^E nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshapecanvas')")

^K OnDragLeft

`wxShapeCanvas::OnDragRight`

`void OnDragRight(bool draw, double x, double y, int keys = 0)`^K

Called when a right-button drag event on the canvas background is detected by `OnEvent`. You may override this member; by default it does nothing.

`draw` is alternately `TRUE` and `FALSE`, to assist drawing and erasing.

`keys` is a bit list of the following:

{bmc bullet.bmp} `KEY_SHIFT`

{bmc bullet.bmp} `KEY_CTRL`

See also [`wxShapeCanvas::OnBeginDragRight`](#), [`wxShapeCanvas::OnEndDragRight`](#).

`wxShapeCanvas::OnDragRight`

`wxshapecanvasondragright`

`rowse00342`

`wxShapeCanvas OnDragRight`

`enableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshapecanvas')")`

`OnDragRight`

`$#+K!` wxShapeCanvas::OnLeftClick

`void OnLeftClick(double x, double y, int keys = 0)`^K

Called when a left click event on the canvas background is detected by OnEvent. You may override this member; by default it does nothing.

keys is a bit list of the following:

{bmc bullet.bmp} KEY_SHIFT

{bmc bullet.bmp} KEY_CTRL

`w`xShapeCanvas::OnLeftClick
`w`xshapecanvasonleftclick
`b`rowse00343
`K` wxShapeCanvas OnLeftClick
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshapecanvas')")
`K` OnLeftClick

`wxShapeCanvas::OnRightClick`

`void OnRightClick(double x, double y, int keys = 0)`^K

Called when a right click event on the canvas background is detected by `OnEvent`. You may override this member; by default it does nothing.

`keys` is a bit list of the following:

{bmc bullet.bmp} `KEY_SHIFT`

{bmc bullet.bmp} `KEY_CTRL`

^w`wxShapeCanvas::OnRightClick`
^w`wxshapecanvasonrightclick`
^b`rowse00344`
^K `wxShapeCanvas OnRightClick`
^E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshapecanvas')")`
^K `OnRightClick`

`$#+K!` **wxShapeCanvas::Redraw**

void Redraw()^K

Calls wxDiagram::Redraw.

^wxShapeCanvas::Redraw

^topic257

^browse00345

^K wxShapeCanvas Redraw

^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshapecanvas')")

^K Redraw

`$#+K!` wxShapeCanvas::RemoveShape

`void RemoveShape(wxShape *shape)K`

Calls wxDiagram::RemoveShape.

`w`xShapeCanvas::RemoveShape

`t`opic258

`b`rowse00346

`K` wxShapeCanvas RemoveShape

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshapecanvas')")

`K` RemoveShape

`wxShapeCanvas::SetDiagram`

`void SetDiagram(wxDiagram *diagram)`

Sets the diagram associated with this diagram.

`wxShapeCanvas::SetDiagram`

`topic259`

`browse00347`

`wxShapeCanvas SetDiagram`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshapecanvas')")`

`SetDiagram`

`wxShapeCanvas::Snap`

`void Snap(double *x, double *y)`

Calls `wxDiagram::Snap`.

`wxShapeCanvas::Snap`

`topic260`

`browse00348`

`wxShapeCanvas Snap`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshapecanvas')")`

`Snap`

`wxShapeEvtHandler::m_handlerShape`

`wxShape* m_handlerShape`^K

Pointer to the shape associated with this handler.

`wxShapeEvtHandler::m_handlerShape`

`topic261`

`browse00350`

`wxShapeEvtHandler m_handlerShape`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshapeevthandler')")`

`m_handlerShape`

`wxShapeEvtHandler::m_previousHandler`

`wxShapeEvtHandler* m_previousHandler`^K

Pointer to the previous handler.

`wxShapeEvtHandler::m_previousHandler`

`topic262`

`browse00351`

`wxShapeEvtHandler m_previousHandler`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshapeevthandler')")`

`m_previousHandler`

`wxShapeEvtHandler::wxShapeEvtHandler`

`void wxShapeEvtHandler(wxShapeEvtHandler *previous = NULL, wxShape *shape = NULL)`^K

Constructs a new event handler.

`wxShapeEvtHandler::wxShapeEvtHandler`
topic263
browse00352
`wxShapeEvtHandler wxShapeEvtHandler`
EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshapeevthandler')")
`wxShapeEvtHandler`

`$#+K!` **wxShapeEvtHandler::~~wxShapeEvtHandler**

void ~wxShapeEvtHandler()^K

Destructor.

`w` wxShapeEvtHandler::~~wxShapeEvtHandler

`t`opic264

`b`rowse00353

`K` wxShapeEvtHandler ~wxShapeEvtHandler

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshapeevthandler')")

`K` ~wxShapeEvtHandler

`$#+K!` **wxShapeEvtHandler::CopyData**

void CopyData(wxShapeEvtHandler& *handler*)^K

A virtual function to copy the data from this object to *handler*. Override if you derive from wxShapeEvtHandler and have data to copy.

`w`xShapeEvtHandler::CopyData
`w`xshapeevthandlercopydata
`b`rowse00354
`K` wxShapeEvtHandler CopyData
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshapeevthandler')")
`K` CopyData

`$#+K!` wxShapeEvtHandler::CreateNewCopy

`wxShapeEvtHandler*` CreateNewCopy()^K

Creates a new event handler object of the same class as this object, and then calls `wxShapeEvtHandler::CopyData`.

`w`xShapeEvtHandler::CreateNewCopy
`w`xshapeevthandlercreatenewcopy
`b`rowse00355
`K` wxShapeEvtHandler CreateNewCopy
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshapeevthandler')")
`K` CreateNewCopy

`wxShapeEvtHandler::GetPreviousHandler`

`wxShapeEvtHandler* GetPreviousHandler() const`

Returns the previous handler.

`wxShapeEvtHandler::GetPreviousHandler`

`wxshapeevthandlergetprevioushandler`

`browse00356`

`K wxShapeEvtHandler GetPreviousHandler`

`K GetPreviousHandler`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshapeevthandler')")`

`wxShapeEvtHandler::GetShape`

`wxShape* GetShape() const`

Returns the shape associated with this handler.

`wxShapeEvtHandler::GetShape`

`wxshapeevthandlergetshape`

`rowse00357`

`wxShapeEvtHandler GetShape`

`GetShape`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshapeevthandler')")`

`wxShapeEvtHandler::OnBeginDragLeft`

`void OnBeginDragLeft(double x, double y, int keys=0, int attachment = 0)`^K

Called when the user is beginning to drag using the left mouse button.

`wxShapeEvtHandler::OnBeginDragLeft`

`topic265`

`browse00358`

`wxShapeEvtHandler OnBeginDragLeft`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshapeevthandler')")`

`OnBeginDragLeft`

`$#+K!` **wxShapeEvtHandler::OnBeginDragRight**

void OnBeginDragRight(double x, double y, int keys=0, int attachment = 0)^K

Called when the user is beginning to drag using the right mouse button.

`w`xShapeEvtHandler::OnBeginDragRight

`t`opic266

`b`rowse00359

`K` wxShapeEvtHandler OnBeginDragRight

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshapeevthandler')")

`K` OnBeginDragRight

`wxShapeEvtHandler::OnBeginSize`

`void OnBeginSize(double width, double height)`

Called when a shape starts to be resized.

`wxShapeEvtHandler::OnBeginSize`

`topic267`

`browse00360`

`wxShapeEvtHandler OnBeginSize`

`enableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshapeevthandler')")`

`OnBeginSize`

^{S#+K!}wxShapeEvtHandler::OnChangeAttachment

void OnChangeAttachment(int *attachment*, wxLineShape* *line*, wxList& *ordering*)^K

Override this to prevent or intercept line reordering. wxShape's implementation of this function calls wxShape::ApplyAttachmentOrdering to apply the new ordering.

^wxShapeEvtHandler::OnChangeAttachment
^wxshapeevthandleronchangeattachment
^browse00361
^K wxShapeEvtHandler OnChangeAttachment
^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshapeevthandler')")
^K OnChangeAttachment

`$#+K!` **wxShapeEvtHandler::OnDragLeft**

void OnDragLeft(**bool** *draw*, **double** *x*, **double** *y*, **int** *keys=0*, **int** *attachment = 0*)^K

Called twice when the shape is being dragged, once to allow erasing the old image, and again to allow drawing at the new position.

`w`xShapeEvtHandler::OnDragLeft
`t`opic268
`b`rowse00362
`K` wxShapeEvtHandler OnDragLeft
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshapeevthandler')")
`K` OnDragLeft

`wxShapeEvtHandler::OnDragRight`

`void OnDragRight(bool draw, double x, double y, int keys=0, int attachment = 0)`^K

Called twice when the shape is being dragged, once to allow erasing the old image, and again to allow drawing at the new position.

`wxShapeEvtHandler::OnDragRight`
topic269
browse00363
K wxShapeEvtHandler OnDragRight
E nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshapeevthandler')")
K OnDragRight

`wxShapeEvtHandler::OnDraw`

`void OnDraw(wxDC& dc)`

Defined for each class to draw the main graphic, but not the contents.

`wxShapeEvtHandler::OnDraw`

`topic270`

`browse00364`

`wxShapeEvtHandler OnDraw`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshapeevthandler')")`

`OnDraw`

`##+K!` **wxShapeEvtHandler::OnDrawContents**

void OnDrawContents(wxDC& dc)^K

Defined for each class to draw the contents of the shape, such as text.

`w`xShapeEvtHandler::OnDrawContents

`t`opic271

`b`rowse00365

`K` wxShapeEvtHandler OnDrawContents

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshapeevthandler')")

`K` OnDrawContents

`wxShapeEvtHandler::OnDrawControlPoints`

`void OnDrawControlPoints(wxDC& dc)`

Called when the shape's control points (handles) should be drawn.

`wxShapeEvtHandler::OnDrawControlPoints`

`topic272`

`browse00366`

`wxShapeEvtHandler OnDrawControlPoints`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshapeevthandler')")`

`OnDrawControlPoints`

wxShapeEvtHandler::OnDrawOutline

void OnDrawOutline(wxDC& dc)^K

Called when the outline of the shape should be drawn.

^wxShapeEvtHandler::OnDrawOutline
^topic273
^browse00367
^K wxShapeEvtHandler OnDrawOutline
^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshapeevthandler')")
^K OnDrawOutline

`$#+K!` **wxShapeEvtHandler::OnEndDragLeft**

void OnEndDragLeft(double x, double y, int keys=0, int attachment = 0)^K

Called when the user is stopping dragging using the left mouse button.

`w`xShapeEvtHandler::OnEndDragLeft
`t`opic274
`b`rowse00368
`K` wxShapeEvtHandler OnEndDragLeft
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshapeevthandler')")
`K` OnEndDragLeft

`wxShapeEvtHandler::OnEndDragRight`

`void OnEndDragRight(double x, double y, int keys=0, int attachment = 0)`^K

Called when the user is stopping dragging using the right mouse button.

`wxShapeEvtHandler::OnEndDragRight`

`topic275`

`browse00369`

`wxShapeEvtHandler OnEndDragRight`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshapeevthandler')")`

`OnEndDragRight`

`wxShapeEvtHandler::OnEndSize`

`void OnEndSize(double width, double height)`

Called after a shape is resized.

`wxShapeEvtHandler::OnEndSize`

`topic276`

`browse00370`

`wxShapeEvtHandler OnEndSize`

`enableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshapeevthandler')")`

`OnEndSize`

`wxShapeEvtHandler::OnErase`

`void OnErase(wxDC& dc)`

Called when the whole shape should be erased.

`wxShapeEvtHandler::OnErase`

`topic277`

`browse00371`

`wxShapeEvtHandler OnErase`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshapeevthandler')")`

`OnErase`

`wxShapeEvtHandler::OnEraseContents`

`void OnEraseContents(wxDC& dc)`^K

Called when the contents should be erased.

`wxShapeEvtHandler::OnEraseContents`

`topic278`

`browse00372`

`wxShapeEvtHandler OnEraseContents`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshapeevthandler')")`

`OnEraseContents`

`wxShapeEvtHandler::OnEraseControlPoints`

`void OnEraseControlPoints(wxDC& dc)`

Called when the shape's control points (handles) should be erased.

`wxShapeEvtHandler::OnEraseControlPoints`

`topic279`

`browse00373`

`wxShapeEvtHandler OnEraseControlPoints`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshapeevthandler')")`

`OnEraseControlPoints`

`wxShapeEvtHandler::OnHighlight`

`void OnHighlight(wxDC& dc)`

Called when the shape should be highlighted.

`wxShapeEvtHandler::OnHighlight`

`topic280`

`browse00374`

`wxShapeEvtHandler OnHighlight`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshapeevthandler')")`

`OnHighlight`

`$#+K!` **wxShapeEvtHandler::OnLeftClick**

void OnLeftClick(double x, double y, int keys = 0, int attachment = 0)^K

Called when the shape receives a left mouse click event.

`w`xShapeEvtHandler::OnLeftClick

`t`opic281

`b`rowse00375

`K` wxShapeEvtHandler OnLeftClick

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshapeevthandler')")

`K` OnLeftClick

`wxShapeEvtHandler::OnMoveLink`

`void OnMoveLink(wxDC& dc, bool moveControlPoints=TRUE)`^K

Called when the line attached to an shape need to be repositioned, because the shape has moved.

`wxShapeEvtHandler::OnMoveLink`

`topic282`

`browse00376`

`wxShapeEvtHandler OnMoveLink`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshapeevthandler')")`

`OnMoveLink`

`$#+K!` **wxShapeEvtHandler::OnMoveLinks**

void OnMoveLinks(wxDC& dc)^K

Called when the lines attached to an shape need to be repositioned, because the shape has moved.

`w`xShapeEvtHandler::OnMoveLinks

`t`opic283

`b`rowse00377

`K` wxShapeEvtHandler OnMoveLinks

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshapeevthandler')")

`K` OnMoveLinks

`$#+K!` **wxShapeEvtHandler::OnMovePost**

bool OnMovePost(wxDC& dc, double x, double y, double oldX, double oldY, bool display = TRUE)^K

Called just after the shape receives a move request.

`w`xShapeEvtHandler::OnMovePost
`t`opic284
`b`rowse00378
`K` wxShapeEvtHandler OnMovePost
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshapeevthandler')")
`K` OnMovePost

`$#+K!` **wxShapeEvtHandler::OnMovePre**

bool OnMovePre(wxDC& dc, double x, double y, double oldX, double oldY, bool display = TRUE)^K

Called just before the shape receives a move request. Returning TRUE allows the move to be processed; returning FALSE vetoes the move.

`w`xShapeEvtHandler::OnMovePre

`t`opic285

`b`rowse00379

`K` wxShapeEvtHandler OnMovePre

`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshapeevthandler')")

`K` OnMovePre

`wxShapeEvtHandler::OnRightClick`

`void OnRightClick(double x, double y, int keys = 0, int attachment = 0)`^K

Called when the shape receives a mouse mouse click event.

`wxShapeEvtHandler::OnRightClick`

`topic286`

`browse00380`

`wxShapeEvtHandler OnRightClick`

`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshapeevthandler')")`

`OnRightClick`

wxShapeEvtHandler::OnSize

void OnSize(double x, double y)^K

Called when the shape receives a resize request.

^wxShapeEvtHandler::OnSize

^topic287

^browse00381

^K wxShapeEvtHandler OnSize

^EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshapeevthandler')")

^K OnSize

`$$$K! wxShapeEvtHandler::OnSizingBeginDragLeft`

`void OnSizingBeginDragLeft(wxControlPoint* pt, double x, double y, int keys=0, int attachment = 0)K`

Called when a sizing drag is beginning.

`wxShapeEvtHandler::OnSizingBeginDragLeft`
`topic288`
`browse00382`
`K wxShapeEvtHandler OnSizingBeginDragLeft`
`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshapeevthandler')")`
`K OnSizingBeginDragLeft`

`$#+K!` **wxShapeEvtHandler::OnSizingDragLeft**

void OnSizingDragLeft(wxControlPoint* pt, bool draw, double x, double y, int keys=0, int attachment = 0)^K

Called when a sizing drag is occurring.

`w`xShapeEvtHandler::OnSizingDragLeft
`t`opic289
`b`rowse00383
`K` wxShapeEvtHandler OnSizingDragLeft
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxshapeevthandler')")
`K` OnSizingDragLeft

`wxShapeEvtHandler::OnSizingEndDragLeft`

`void OnSizingEndDragLeft(wxControlPoint* pt, double x, double y, int keys=0, int attachment = 0)`^K

Called when a sizing drag is ending.

`wxShapeEvtHandler::OnSizingEndDragLeft`

`topic290`

`browse00384`

`wxShapeEvtHandler OnSizingEndDragLeft`

`enableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshapeevthandler')")`

`OnSizingEndDragLeft`

`wxShapeEvtHandler::SetPreviousHandler`

`void SetPreviousHandler(wxShapeEvtHandler* handler)`^K

Sets the previous handler.

^w`wxShapeEvtHandler::SetPreviousHandler`
^w`wxshapeevthandler::setprevioushandler`
^b`rowse00385`
^K`wxShapeEvtHandler SetPreviousHandler`
^E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshapeevthandler')")`
^K`SetPreviousHandler`

`wxShapeEvtHandler::SetShape`

`void SetShape(wxShape* shape)`

Sets the shape for this handler.

`wxShapeEvtHandler::SetShape`
`wxshapeevthandlersetshape`
`rowse00386`
`wxShapeEvtHandler SetShape`
`enableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxshapeevthandler')")`
`SetShape`

`##+K! wxTextShape::wxTextShape`

`void wxTextShape(double width = 0.0, double height = 0.0)`^K

Constructor.

`w`xTextShape::wxTextShape
`t`opic291
`b`rowse00388
`K` wxTextShape wxTextShape
`E`nableButton("Up");ChangeButtonBinding("Up", "JumpId(`ogl.hlp', `wxttextshape')")
`K` wxTextShape

`$#+K! wxTextShape::~~wxTextShape`

`void ~wxTextShape()K`

Destructor.

`wxTextShape::~~wxTextShape`

`topic292`

`browse00389`

`K wxTextShape ~wxTextShape`

`E nableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `wxttextshape')")`

`K ~wxTextShape`

`$#+K!::wxOGLInitialize`

`void wxOGLInitialize()`^K Initializes OGL.

`·:wxOGLInitialize`
`topic293`
`browse00391`
`K wxOGLInitialize`
`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `functions')")`
`K wxOGLInitialize`

`$#+K!::wxOGLCleanUp`

`void wxOGLCleanUp()`^K Cleans up OGL.

`·:wxOGLCleanUp`
`topic294`
`browse00392`
`K wxOGLCleanUp`
`EnableButton("Up");ChangeButtonBinding("Up", "JumpId(^ogl.hlp', `functions')")`
`K wxOGLCleanUp`

